

DESCRIPTION:

Air Lift is a highly specialized detergent system formulated for the removal of soils and deposits caused by industrial airborne pollutants. It will quickly and effectively remove these soils from a wide variety of surfaces, including painted automotive finishes. Special detergents and penetrating agents make this product easy to use and rinse. Safely removes petroleum deposits, rail dusts, water spots, jet aircraft soot, and other acid soluble contaminants.

DIRECTIONS:

Do not apply Airlift to a hot surface. Allow surface to cool, or cool with hose prior to use. Air Lift is a ready-to-use formulation but may be diluted slightly if soils and deposits are not significant or heavy. Apply to surfaces liberally using a brush or sprayer. Allow product to remain on surface for 3 to 5 minutes. Keep surfaces wet and apply agitation if necessary. Rinse very thoroughly with water to flush away contaminants. It is recommended that the surface then be washed with a suitable alkaline detergent. Ask your Wechem representative for a product recommendation.

Note: Air Lift will not harm most surfaces, including painted surfaces. However, we recommend pre-testing Air Lift on an inconspicuous spot prior to full scale application. Do not allow formulation to dry on surface.



AIR LIFT™

Industrial Fallout and Soot Remover

**KEEP OUT OF REACH OF CHILDREN.
FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY.**

(SEE RIGHT PANEL FOR ADDITIONAL CAUTIONS AND FIRST AID STATEMENTS.)

**To Reorder:
WECHEM, INC.**

**5734 Susitna Drive Harahan, LA 70123
(504) 733-1152 * 1-800-426-0512
FAX: (504) 733-2218 * www.wechem.com**

5/00

CAUTION:

Corrosive. Avoid contact with skin and eyes. Can cause eye and skin irritation. Harmful if swallowed or inhaled. Do not mix with any other cleaner or chemical.

FIRST AID:

EYES: Flush with water for at least 15 minutes. Seek medical attention.

SKIN: Wash with soap and water. If irritated, seek medical attention.

INGESTION: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.

INHALATION: Remove to fresh air. Resuscitate if necessary. Get medical attention.

CONTAINS:	CAS #:
Oxalic Acid Dihydrate.....	6153-56-6
Ethylene Glycol Monobutyl Ether.....	111-76-2

NFPA		HAZARD RATING:
Health	Fire Hazard	4-EXTREME
Specific Hazard	Reactivity Hazard	3-HIGH
		2-MODERATE
		1-SLIGHT

Proper Shipping Name:
Corrosive Liquid, NOS (Oxalic Acid), 8, UN 1760, PG III

READ MATERIAL SAFETY DATA SHEET BEFORE USE

UNIT OF MEASURE: U.S. GALLONS