

DESCRIPTION:

AL-600 is a modern compound which restores the "like new" appearance to surfaces. This concentrated solution quickly and effortlessly removes dirt, soot, oxidation and other soils from a wide variety of surfaces including aluminum, stainless steel and some fiberglass. This product is the formulation of choice when economy and speed are essential.

DIRECTIONS:

Wet down surface with hose to cool. Apply solution mixed according to instructions below. Start at the bottom or floor level and work upward. Cover only one eight to ten foot section at a time. Allow sufficient soak time - two to four minutes at 80-100 degrees air temperature, three to six minutes at 70-80 degrees and six to ten minutes at 35-70 degrees. Rinse, starting at top and work down.

For best results, solution must be rinsed while still wet. If drying occurs, reapply solution before rinsing. For extremely soiled or oxidized units, it may be necessary to make a second application. Always store solution in cool, dry area. **Avoid contact with glass.**

- ◆ For heavily soiled or badly corroded aluminum, use one part AL-600 to five to ten parts water.
- ◆ For new or moderately soiled aluminum, use one part AL-600 to 40 to 50 parts water.
- ◆ For stainless steel, use one to five dilution on heavily soiled surfaces, one to ten on lightly soiled surfaces and up to one to forty dilution for new surfaces.

Net Contents: _____

Batch: _____



AL-600™

Aluminum Brightener and Cleaner

Highly concentrated
Instantly cleans and brightens
Removes oxides, grease, carbon, oil, soot and
other soils

Danger! Causes Severe Burns!

KEEP OUT OF REACH OF CHILDREN.
FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY.
(SEE RIGHT PANEL FOR ADDITIONAL CAUTIONS AND FIRST AID STATEMENTS.)

To Reorder:
WECHEM, INC.

5734 Susitna Drive Harahan, LA 70123
(504) 733-1152 • 1-800-426-0512

FAX: (504) 733-2218 * www.wechem.com

7/00

☠ DANGER-POISON ☠

WARNING:

To use this product the following requirements are necessary: A) use a face shield, rubber gloves, rubber apron and rubber boots; B) have adequate ventilation; C) avoid eye and skin contact; D) do not breath spray mist; E) when spraying, use NIOSH approved respirator system; F) shower or water hose should be available. **DO NOT MIX WITH ANYTHING EXCEPT WATER.**

FIRST AID:

EYES: Speed of action is of primary importance. Flush with water for at least 15 minutes and call a physician.


SKIN: Wash with large amounts of soap and water. If irritation persists, consult a physician.

INGESTION: DO NOT INDUCE VOMITING. Dilute by drinking water. Call a physician immediately.

INHALATION: Remove to fresh air. If breathing has stopped, artificial respiration should be started. Oxygen may be administered, if available. Call a physician. Never give anything by mouth to an unconscious person.

CONTAINS:	CAS #:
Hydrofluoric Acid, Aqueous	7664-39-3
Phosphoric Acid	7664-38-2
Ethylene Glycol Monobutyl Ether.....	111-76-2

NFPA



HAZARD RATING:

4-EXTREME
3-HIGH
2-MODERATE
1-SLIGHT

Proper Shipping Name: Corrosive Liquids, Toxic, N.O.S.
(Hydrofluoric Acid) (Phosphoric Acid), 8, UN 2922, PG II

READ MATERIAL SAFETY DATA SHEET BEFORE USE