

DESCRIPTION

ALLUMINATOR is a modern compound which restores the "like new" appearance to bare aluminum surfaces. This concentrated solution quickly and effortlessly removes dirt, soot, oxidation and other soils from bare aluminum with little to no brushing. It is ideally suited for cleaning and brightening of processing equipment, packaging equipment, structures, and trailers. **ALLUMINATOR** is the formulation of choice when economy and speed are essential.

DIRECTIONS

Wet down surface with hose to cool. Apply solution mixed according to instructions below. Start at the bottom or floor level and work upward. Cover only one eight to ten foot section at a time. Allow sufficient soak time - one to three minutes at 80°-100°F air temperature, two to five minutes at 70°-80°F, and three to six minutes at 35°-70°F. Rinse, starting at top and work down.

For best results, solution must be rinsed while still wet. If drying occurs, reapply solution before rinsing. For extremely soiled or oxidized units, it may be necessary to make a second application. Always store solution in cool, dry area.

▪ **For heavily soiled or badly corroded aluminum:** Use one part **ALLUMINATOR** to five to ten parts water.

▪ **For new or moderately soiled aluminum:** Use one part **ALLUMINATOR** to 40 to 50 parts water.

▪ **For trailer cleaning:** application should be made from bottom to top to avoid streaking. Rinse 15 to 30 seconds after application for clean, bright, "like new" appearance. Brightens most trailers without prior washing or brushing.

***Notice:** Do not use on anodized or highly polished metal surfaces (including aluminum and stainless steel) or allow run off to contact such surfaces as irreversible damage may occur. Should contact occur, flush immediately with water. Keep product off of glass, fiberglass, ceramic and painted surfaces.



Engineered Chemistries
SUPERIOR SOLUTIONS

ALLUMINATOR™

ALUMINUM Cleaner - Brightener - Deoxidizer

- **HIGHLY CONCENTRATED**
- **INSTANTLY CLEANS & BRIGHTENS**
- **REMOVES OXIDES, GREASE, CARBON, OIL, SOOT & OTHER SOILS**

DANGER

CAUSES SEVERE BURNS

KEEP OUT OF REACH OF CHILDREN

FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY.

(SEE RIGHT PANEL FOR ADDITIONAL CAUTIONS AND FIRST AID STATEMENTS.)

NET CONTENTS: U. S. GALLON

4/11

DANGER - POISON



Corrosive: To use this product the following requirements are necessary:

- A) Use a face shield or goggles, rubber gloves, rubber apron and rubber boots
- B) Have adequate ventilation
- C) Avoid skin and eye contact. Do not mix with anything but water.

FIRST AID

EYES: Flush with water for 15 minutes. Seek medical attention.

SKIN: Wash with soap and water. If irritated, seek medical attention.

INHALATION: Remove to fresh air. Resuscitate if necessary. Seek immediate medical attention.

INGESTION: DO NOT INDUCE VOMITING. Drink two large glasses of water. Seek immediate medical attention.

CONTAINS:	CAS#
Hydrofluoric Acid, Aqueous.....	7664-39-3
Phosphoric Acid.....	7664-38-2
Ethylene Glycol Monobutyl Ether.....	111-76-2
Sulfuric Acid.....	7664-93-9

NFPA

Health

Specific Hazard



HAZARD RATING:

4-EXTREME
3-HIGH
2-MODERATE
1-SLIGHT

Proper Shipping Name: Hydrofluoric Acid & Sulfuric Acid Mixture), 8, 6.1, UN1786, PG I

READ MATERIAL SAFETY DATA SHEET BEFORE USE.

WECHEM, INC.
5734 Susitna Dr
Harahan, LA 70123
(504) 733-1152
800-426-0512
FAX (504) 733-2218
WWW.WECHEM.COM



7 38435 20628 4