

DESCRIPTION:

C-130 is designed to perform in tapping, threading, shaping, plaining, drilling, grinding and gear shaving. It offers excellent antiweld performance, extended tool life and superior surface finish, without chlorine and with reduced amounts of sulfur and fat. Its clear, light color allows operator to better see the machined part during the cutting operation. It has a low odor and contains an ISOSYN base stock, which provides better thermal and oxidation stability for longer fluid life. The ISOSYN base stock also increases oil life and creates a safer work environment by increasing the fluid's flash point and lowering exposure to aromatics and product vapor, smoking and misting. The chlorine-free nature of the fluid reduces the cost of disposal at the end of the fluid life.

- ◆ *Ready To Use Formulation*
- ◆ *Anti -Corrosive*
- ◆ *Cools and Lubricates*



C-130™

Cutting and Threading Oil

CAUTION:

KEEP OUT OF REACH OF CHILDREN.
FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY.
(SEE RIGHT PANEL FOR ADDITIONAL CAUTIONS AND FIRST AID STATEMENTS.)

To Reorder:
WECHEM, INC.

5734 Susitna Drive Harahan, LA 70123
(504) 733-1152 * 1-800-426-0512
FAX: (504) 733-2218 * www.wechem.com

UNIT OF MEASURE: U.S. GALLONS

WARNING:

Harmful if swallowed or inhaled. Causes eye irritation. May cause skin irritation. Do not mix with any other cleaner or chemical.

FIRST AID:

EYES: Flush with water for at least 15 minutes. Seek medical attention.
SKIN: Wash with soap and water. If irritated, seek medical attention.
INGESTION: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.
INHALATION: Remove to fresh air. Resuscitate if necessary. Get medical attention.

CONTAINS:

Highly Refined Mineral Oil (C15-C50)..... N/A

CAS:

NEPA

Health

Specific Hazard



HAZARD RATING:

- 4-EXTREME
- 3-HIGH
- 2-MODERATE
- 1-SLIGHT

Proper Shipping Name: Petroleum Oils, Greases