

Threaded Connections • Metal Fittings

Packings • Sleeves • Flanges

Machinery • Pumps • Valves • Manifolds

Heat Exchangers • Compressors • Bushings

Castings • Turbines • Dies

CP 2000 is a premium copper/graphite blend anti-seize formulated to prevent seizing and galling at high temperatures. Temperature-resistant from -40°F to 2000°F. Lubricates and protects most metal fasteners and fittings from corrosion and rust. Eases assembly and disassembly of metal parts while reducing friction and wear.

SUGGESTED APPLICATIONS:

Threaded connections, metal fittings, packings, sleeves, flanges, machinery, pumps, valves, manifolds, heat exchangers, compressors, bushings, castings, turbines, and dies. Many applications exist in chemical plants, oil refineries, power plants, paper mills, automotive assembly plants, waste and water treatment plants and mining facilities.

DIRECTIONS:

Clean threads or application area. Apply thin coating with stiff bristle brush. Assemble parts. To avoid contamination, close container when not using.



Engineered Chemistries
SUPERIOR SOLUTIONS



CP 2000™ COPPER ANTI-SEIZE

MEETS MIL-A-907-E



- Prevents Seizure at High Temps
- Compatible with Soft Metals
- Enables Fast Disassembly even after High Temp Exposure
- Prevents Galling on Steel, Stainless Steel, Titanium, Magnesium and other Hard Metals

CAUTION

KEEP OUT OF REACH OF CHILDREN

FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY.

(SEE RIGHT PANEL FOR ADDITIONAL CAUTIONS AND FIRST AID STATEMENTS.)

NET WT 8 OZ (227G)

4/11

CAUTION: Possible eye and skin irritant. Do not get in eyes or on skin.

FIRST AID

EYES: Flush eyes with water for 15 minutes. Seek medical attention.

SKIN: Wash with soap and water. If irritated, seek medical attention.

INHALATION: Remove to fresh air. Resuscitate if necessary. Get medical attention.

INGESTION: Do not induce vomiting. Drink two large glasses of water. Get immediate medical attention.

CONTAINS:	CAS #
Graphite.....	7782-42-5
Copper Compound.....	7440-50-8
Paraffinic Oil.....	64742-65-0

NFPA



HAZARD RATING:

- 4-EXTREME
- 3-HIGH
- 2-MODERATE
- 1-SLIGHT
- 0-INSIGNIFICANT

Proper Shipping Name: Lubricants, Greases

READ MATERIAL SAFETY DATA SHEET BEFORE USE.

WECHEM, INC.
5734 Susitna Dr.
Harahan, LA 70123
504.733.1152
1.800.426.0512
FAX 504.733.2218
www.wechem.com



7 38435 20633 8