

**DESCRIPTION:**

A high purity, high dielectric, rapidly evaporating, non-flammable aerosol spray contact and circuit board cleaner. Specially formulated for removing oil, grease, condensation, dust and other particulate matter from sensitive electronic parts. Quick drying formula will not harm most plastics, paints or rubbers.

This solvent system has tested safe on: Neoprene, Buna, Silicone, Butyl and Natural Rubber, Nylon, Hypalon®, PTFE, PVC, Polyurethane, Polystyrene, Styrene, Polyethylene, Polypropylene, Epoxy and ABS.

\*Dielectric Strength testing done by Method ASTM D877 (0.10 inch gap)

**NOTE:**

If there is any doubt as to the material construction this product is to be used on, test on a small hidden surface prior to general use. Not recommended for use on Acrylic or Stressed Polycarbonate materials. Pre-testing is strongly suggested.

Zero residue formula is also excellent for cleaning and degreasing metal parts and fittings.

**USE ON:**

Circuit Boards, Wire Terminals, Relays, Switches, Contacts, Circuit Breakers, Tuners, Potentiometers, Cable Ends and Receptacles, Control Panels, Motors and other Electronic and Electrical Equipment.

**DIRECTIONS:**

Spray directly onto surface, holding can close to work. For hard to reach areas, insert extension tube into actuator orifice. Allow components to dry completely before applying current.



# CIRCUIT WASH™

## ELECTRONIC CONTACT CLEANER and DEGREASER

- **NON-FLAMMABLE**
- **NON-CORROSIVE**
- **SAFE ON MOST PLASTICS**
- **DRIES FAST**
- **ZERO RESIDUE**
- **EPA SNAP APPROVED**
- **VOG EXEMPT**
- **30,000 VOLT DIELECTRIC STRENGTH\***

NET WT. 10 OZ. (283 Grams)

**CAUTION:** CONTENTS UNDER PRESSURE. SEE OTHER CAUTIONS ON SIDE PANEL.

REV 01-08

**CAUTION:** Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F. Chemical contact with flames or extremely hot surfaces can cause ignition, vapor decomposition and toxic gas.

**FIRST AID:**

**IF EYE CONTACT:** In case of contact, immediately flush with large amounts of lukewarm water for at least 15 minutes while holding upper and lower lids open. Get medical attention.

**IF SKIN CONTACT:** In case of contact, immediately flush skin with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Treat for frostbite if necessary by gently warming affected area. If irritation persists, get medical attention.

**EXCESSIVE INHALATION:** Immediately remove to fresh air. If not breathing, give artificial respiration. Get medical attention.

**IF INGESTED:** Ingestion is not likely to occur. If it does, do not induce vomiting. Get medical attention.

**KEEP OUT OF REACH OF CHILDREN**

For further information consult Material Safety Data Sheet.

CONTAINS:	CAS#
3,3-Dichloro-1,1,1,2,2	
-pentafluoropropane.....	422-56-0
1,1,1,2-Tetrafluoroethane.....	811-97-2
1,3-Dichloro-1,1,2,2,3	
-pentafluoropropane.....	507-55-1

NFPA	HAZARD RATING:
Health 1	Flammability 0
Special 1	Reactivity 1
	4-EXTREME
	3-HIGH
	2-MODERATE
	1-SLIGHT
	0-INSIGNIFICANT

**DOT NAME:** Consumer Commodity, ORM-D

READ MATERIAL SAFETY DATA SHEET BEFORE USE

To Reorder:

**WECHEM, INC.**

5734 Susitna Drive, Harahan, LA 70123

LOCAL: (504) 733-1152

FAX: (504) 733-2218

1-800-426-0512

www.wechem.com