

DESCRIPTION:

D-Grease is a heavy duty solvent degreaser. It is ideal for use in applications where water based detergents are ineffective. This formulation contains a blend of high grade solvents, penetrating agents, wetting agents and emulsifiers. Use **D-Grease** to remove the most stubborn contaminants, including: heavy base petroleum fuel oil, grease, oil base coatings, tar, cosmoline, carbon, automotive fluids and other similar soils.

DIRECTIONS:

D-Grease is simple and easy to use. It was formulated for direct application and removal from the surface. The user only needs to apply the product to the surface (spray on, wipe on, or brush on) and allow it to soak into the soil. The solvent action of the formulation will liquify and lift the soil from the surface, allowing for easy removal.

Heavy degreasing: Use compound undiluted or mix 1 to 3 parts with kerosene, or mineral spirits. Medium degreasing: Use compound diluted 4 to 6 parts with kerosene, or mineral spirits. Allow product to soak for 3 to 5 minutes, agitate with brush if needed, and flush with high pressure water. Works on automobiles, trucks, tractors, farm equipment, fork lifts, industrial and manufacturing machinery, stainless steel, tar and asphalt equipment, concrete floors, filters, grease traps, bearings, parts, etc. May be used on any surface not harmed by kerosene.

NET CONTENTS: U.S. GALLONS



D-GREASE™

Solvent Degreaser

Water Flushable Fast Solvent Action

WARNING:
KEEP OUT OF REACH OF CHILDREN.
FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY.
(SEE RIGHT PANEL FOR ADDITIONAL CAUTIONS AND FIRST AID STATEMENTS.)

To Reorder:
WECHEM, INC.
5734 Susitna Drive, Harahan, LA 70123
(504) 733-1152 * TOLL FREE: 1-800-426-0512
FAX: (504) 733-2218 * www.wechem.com

3/99

CAUTION :

Combustible liquid. Warning: HARMFUL if swallowed. Wash thoroughly after handling. Causes eye irritation. Avoid contact with eyes. Caution: May cause skin irritation. Avoid contact with skin and clothing. Wash thoroughly after handling. Use only with adequate ventilation. Avoid prolonged breathing of vapor.

FIRST AID:

EYES: Immediately flush with water for 15 minutes.
SKIN: Wash with soap and water
INHALATION: Remove to fresh air. If breathing stops, give artificial respiration.
INGESTION: DO NOT INDUCE VOMITING. Get medical attention immediately.

CONTAINS:		CAS #:	
Petroleum Naphtha	64742-88-7	2-Butoxyethanol	111-76-2
NFPA		HAZARD RATING:	
Health		4-EXTREME	
		3-HIGH	
		2-MODERATE	
		1-SLIGHT	
Specific Hazard			

READ MATERIAL SAFETY DATA SHEET BEFORE USE