

**DESCRIPTION**

**E-Strip** is the next generation, environmentally safe, user friendly product for removing paint and chemical resistant coatings from surfaces. *E-Strip* does not contain Methylene Chloride, MEK, or other harsh flammable chemicals. The formulation has been specifically developed to remove multiple layers of oil and latex paints, but will also remove many other coatings like: epoxies, urethanes, elastomers and chlorinated rubber. **E-Strip** is designed for use on a variety of substrates including: wood, brick, stone, metal, graphite and steel, and is ideal for use in removing lead paint because it does not evaporate under normal conditions. *E-Strip* is a gel based formula designed to spray and stick to vertical surfaces without runoff.

**DIRECTIONS**

**Paint Stripping** - Test items to be stripped for compatibility. Spray or brush on a thin layer of **E-Strip** and monitor activity, watching for paint to bubble. Rinse, scrape or wipe away residue. Always use solvent safe eyeshields, boots and gloves and avoid skin contact.

**Dilution** - **E-Strip** contains no water and is intended to be used undiluted. Apply with brush or sprayer. Test all sprayers, brushes and surfaces to be treated for solvent compatibility. Avoid contact with plastics.

**Wood and Tile Floors** - Spot test for finish compatibility prior to use. Spray or pour on flooring and allow 15 to 45 minutes to activate. Monitor activity. Dwell times may be extended up to 24 hours with no adverse effects. Wash or brush away old finish or remove with suitable extraction equipment. Properly dispose of residue. For wood surfaces, be careful not to allow product to penetrate into wood. Surface must be thoroughly cleaned prior to refinishing.



- \* *Non-Methylene Chloride*
- \* *Non-MEK*
- \* *Non-Flammable*
- \* *Gel Based Formula*

**CAUTION**  
**KEEP OUT OF REACH OF CHILDREN**  
**FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY.**  
(SEE RIGHT PANEL FOR ADDITIONAL CAUTIONS AND FIRST AID STATEMENTS.) 01/10

**CAUTION**

*Do not take internally. Avoid contact with eyes. Avoid breathing vapors. Vapor is heavier than air and may collect in low lying areas.*

**FIRST AID**

**EYES:** Do not rub eyes. Flush with water for 15 minutes. If irritated, seek medical attention.  
**SKIN:** Wash with soap and water. If irritated, seek medical attention.  
**INHALATION:** Remove to fresh air. Resuscitate if necessary. Get medical attention.  
**INGESTION:** Induce vomiting. Get immediate medical attention.

<b>NFPA</b>		<b>HAZARD RATING:</b>
		<b>4-EXTREME</b>
		<b>3-HIGH</b>
		<b>2-MODERATE</b>
		<b>1-SLIGHT</b>

To Reorder:  
**WECEM, INC.**  
5734 Susitna Dr. \* Harahan, LA 70123  
(504) 733-1152 \* 1-800-426-0512  
FAX: (504) 733-2218 \* WWW.WECEM.COM

**MADE IN THE USA**

**READ MATERIAL SAFETY DATA SHEET BEFORE USE**

**NET CONTENTS: 32 FL. OZ. BATCH #**