

DESCRIPTION:

Excel 125 is a residue-free, fast drying formula that quickly dissolves grease/oils and rinses away dirt and grime without injury to working parts. Contains an accepted replacement for 1,1,1-Trichloroethane under the EPA SNAP program. Contains no CFC's or ozone depleting chemicals. High dielectric strength combined with non-flammability make this the only degreaser safe for use on motors, generators, relays and control panels.

USES:

Automotive Parts, Diesel Engines, Marine Equipment, Aircraft Parts, Industrial Equipment, Heating and Air Conditioning Equipment, Refrigeration Equipment, Generators, Motors, Windings, Power Tools

DIRECTIONS:

Saturate area to be cleaned. Wipe off or allow to air dry. For heavily encrusted areas, brush, then rinse off with a second application.

Net Contents: _____

Batch: _____

READ MATERIAL SAFETY DATA SHEET BEFORE USE



EXCEL 125™

Solvent Degreaser & Electrical Equipment Cleaner

- Non-Flammable
- High Dielectric Strength
- Fast-Drying
- Residue-Free

WARNING: VAPOR HARMFUL

KEEP OUT OF REACH OF CHILDREN.

FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY.
(SEE RIGHT PANEL FOR ADDITIONAL CAUTIONS AND FIRST AID STATEMENTS.)

To Reorder:

WECHEM, INC.

5734 Susitna Drive Harahan, LA 70123

LOCAL: (504) 733-1152 ■ FAX: (504) 733-2218

1-800-426-0512 ■ www.wechem.com

7/00

CAUTION:

Do not breathe vapors. High vapor concentrations can cause dizziness, unconsciousness or death. Long-term overexposure may cause liver/kidney injury and possible central nervous system damage. Use with adequate ventilation. Ventilation must be sufficient to limit employee exposure to Trichloroethylene below permissible limits. Observance of lower limits is advisable. (See below.) Avoid contact with eyes. Will cause irritation and pain. Avoid prolonged or repeated contact with skin. Do not swallow. Swallowing may cause injury or death. Do not eat, drink or smoke in work areas.

OSHA Permissible Exposure Limits	50ppm, 8-hour TWA, 100-200 ppm periodic excursions allowed providing 8-hour TWA is at or below 100ppm. 200-300 ppm excursions allowed for maximum of 5 minutes in any 2-hour period; 300 ppm maximum allowable concentration (must not be exceeded).
---	---

29 CFR 1910 1000
Table Z-2

FIRST AID:

EYES: Flush eyes with plenty of water for at least 15 minutes.


SKIN: Flush with soap and water for at least 15 minutes while removing contaminated clothing and shoes. If irritation occurs, consult a physician. Thoroughly clean contaminated clothing and shoes before reuse or discard

INHALATION: Remove to fresh air. If not breathing, give artificial respiration, preferably mouth to mouth. If breathing is difficult, give oxygen. Call a physician.

INGESTION: If conscious: Drink large quantities of water. Do not induce vomiting. Take immediately to hospital or physician. If unconscious or in convulsions, take immediately to a hospital. Do not attempt to give anything by mouth to an unconscious person.

CONTAINS:	CAS #:
Trichloroethylene	79-01-6
Solvent Naphtha	64742-88-7

NFPA



HAZARD RATING:

- 4-EXTREME
- 3-HIGH
- 2-MODERATE
- 1-SLIGHT

Proper Shipping Name: Trichloroethylene, 6.1, UN 1710, PG III