

DESCRIPTION

EXCEL is a residue free, fast drying formula that quickly dissolves grease/oils and rinses away dirt and grime without injury to working parts. Contains an accepted replacement for 1,1,1-Trichloroethane under the EPA SNAP program. Contains no CFC's or ozone depleting chemicals. High dielectric strength combine with non-flammability make this degreaser safe for use on motors, generators, relays and control panels.

USES

Automotive Parts
Diesel Engines
Marine Equipment
Aircraft Parts
Industrial Equipment
Heating & Air Conditioning Equipment
Refrigeration Equipment
Generators
Motors
Winding
Power Tools

DIRECTIONS

Saturate area to be cleaned. Wipe off or allow to air dry. For heavily encrusted areas, brush then rinse off with a second application.



EXCEL 125

**SOLVENT DEGREASER &
ELECTRICAL EQUIPMENT
CLEANER**

**NON-FLAMMABLE
HIGH DIELECTRIC STRENGTH
FAST DRYING
RESIDUE FREE**

**WARNING: VAPOR HARMFUL
KEEP OUT OF REACH OF CHILDREN.
FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY.**
(SEE RIGHT PANEL FOR ADDITIONAL CAUTIONS AND FIRST AID STATEMENTS.)

NET CONTENTS: U.S. GALLON

CAUTION

DO NOT BREATH VAPORS. High vapor concentrations can cause dizziness, unconsciousness or death. Long-term over-exposure may cause liver/kidney injury and possible central nervous system damage. Use with adequate ventilation. Ventilation must be sufficient to limit employee exposure to Trichloroethylene below permissible limits. Observance of lower limits is advisable. (See below) Avoid contact with eyes. Will cause irritation and pain. Avoid prolonged or repeated contact with skin. Do not swallow. Swallowing may cause injury or death. Do not eat, drink or smoke in work areas.

OSHA Permissible Exposure Limits

29 CFR 1910 1000
TABLE Z-2

50ppm, 8-hour TWA, 100-200 ppm periodic excursions allowed providing 8-hour TWA is at or below 100 ppm. 200-300 ppm excursions allowed for maximum of 5 minutes in any 2-hour period; 300 ppm maximum allowable concentration (must not be exceeded).

FIRST AID

EYES - Flush with water for 15 minutes. Irritated, seek medical attention.

SKIN - Wash with soap and water. If irritated seek medical attention.

INHALATION - Remove to fresh air. Resuscitate if necessary. Seek medical attention.

INGESTION - Do not induce vomiting. Get medical attention.

CONTAINS:		CAS#
Trichloroethylene.....		79-01-6
Petroleum Distillate.....		64742-47-8
NFPA	HAZARD RATING:	
Health	Flammability	4-EXTREME
Special Hazard	Reactivity	3-HIGH
		2-MODERATE
		1-SLIGHT
		0-INSIGNIFICANT
Proper Shipping Name: Trichloroethylene, 6.1, UN 1710, PGIII		

READ MATERIAL SAFETY DATA SHEET BEFORE USE.

WECHEM, INC.
5734 Susitna Dr.
Harahan, LA 70123
504.733.1152
800.426.0512
FAX 504.733.2218
www.wechem.com

