

**DESCRIPTION:**

**Excel** is a residue-free, fast drying formula that quickly dissolves grease/oils and rinses away dirt and grime without injury to working parts. Contains an accepted replacement for 1,1,1-Trichloroethane under the EPA SNAP program. Contains no CFC's or ozone depleting chemicals. High dielectric strength combined with non-flammability make this the only degreaser safe for use on motors, generators, relays and control panels.

**USES:**

Automotive Parts, Diesel Engines, Marine Equipment, Aircraft Parts, Industrial Equipment, Heating and Air Conditioning Equipment, Refrigeration Equipment, Generators, Motors, Windings, Power Tools

**DIRECTIONS:**

Saturate area to be cleaned. Wipe off or allow to air dry. For heavily encrusted areas, brush, then rinse off with a second application.

UNIT OF MEASURE: U.S. GALLONS



**EXCEL™**

*Solvent Degreaser & Electrical Equipment Cleaner*

- **Non-Flammable**
- **High Dielectric Strength**
- **Fast-Drying**
- **Residue-Free**

**WARNING:  
VAPOR HARMFUL**

**KEEP OUT OF REACH OF CHILDREN.**  
FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY.  
(SEE RIGHT PANEL FOR ADDITIONAL CAUTIONS AND FIRST AID STATEMENTS.)

To Reorder:  
**WECHEM, INC.**

5734 Susitna Drive Harahan, LA 70123  
LOCAL: (504) 733-1152 ■ FAX: (504) 733-2218  
1-800-426-0512 ■ www.wechem.com

**CAUTION:**  
Do not breathe vapors. High vapor concentrations can cause dizziness, unconsciousness or death. Long-term overexposure may cause liver/kidney injury and possible central nervous system damage. **Use with adequate ventilation.** Ventilation must be sufficient to limit employee exposure to Trichloroethylene below permissible limits. Observance of lower limits is advisable. (See below.) **Avoid contact with eyes.** Will cause irritation and pain. **Avoid prolonged or repeated contact with skin.** Do not swallow. Swallowing may cause injury or death. **Do not eat, drink or smoke in work areas.**

<b>OSHA Permissible Exposure Limits</b>	50ppm, 8-hour TWA, 100-200 ppm periodic excursions allowed providing 8-hour TWA is at or below 100ppm. 200-300 ppm excursions allowed for maximum of 5 minutes in any 2-hour period; 300 ppm maximum allowable concentration (must not be exceeded).
---	--

**FIRST AID:** 29 CFR 1910 1000 Table Z-2  
**EYES:** Flush eyes with plenty of water for at least 15 minutes.  
**SKIN:** Flush with soap and water for at least 15 minutes while removing contaminated clothing and shoes. If irritation occurs, consult a physician. Thoroughly clean contaminated clothing and shoes before reuse or discard  
**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration, preferably mouth to mouth. If breathing is difficult, give oxygen. Call a physician.  
**INGESTION:** If conscious: Drink large quantities of water. **Do not induce vomiting.** Take immediately to hospital or physician. If unconscious or in convulsions, take immediately to a hospital. Do not attempt to give anything by mouth to an unconscious person.

<b>CONTAINS:</b>	<b>CAS #:</b>
Trichloroethylene .....	79-01-6

<b>NFPA</b>		<b>HAZARD RATING:</b>
Health		4-EXTREME
		3-HIGH
		2-MODER-
		ATE
Specific Hazard		1-SLIGHT

Proper Shipping Name: Trichloroethylene, 6.1, UN 1710, PG III

READ MATERIAL SAFETY DATA SHEET BEFORE USE