

HULK SYSTEM-*FS109*

*Heavy Duty
Industrial Cleaner
Readily Biodegradable
Non-Flammable*

DESCRIPTION:

Hulk System FS #109 is highly effective moderately alkaline detergent system that contains no harsh alkaline builders. It was formulated to meet or exceed the tightest standards for employees' safety and/or adverse environmental impact. It is effectively neutral in pH, and only utilizes components that are readily biodegradable.

This material may be used to remove unwanted food processing grease, oils, and soil from surfaces and equipment.



WECHEM, INC.
5734 Susitna Drive
Harahan, LA 70123
(504) 733-1152 1-800-426-0512
FAX: (504) 733-2218
www.wechem.com

UNIT OF MEASURE: U.S. GALLONS

DIRECTIONS:

This product is specifically designed for multi-use cleaning of industrial surfaces. It is suited for use with steam cleaners, pressure washers, floor cleaning equipment and manual cleaning operations. **This product is in concentrated form and may be diluted with water prior to use.** Degree of product strength necessary to clean is directly related to the type of soil being removed and the degree of buildup. Adjust dilution level until achieving optimal cleaning results.

This product is acceptable for use as a general cleaner (A1) on all surfaces in and around food processing areas, where its use is not intended for direct food contact.



KEEP OUT OF REACH OF CHILDREN.
FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY.

SEE RIGHT PANEL FOR ADDITIONAL CAUTIONS
AND FIRST AID STATEMENTS.

CAUTION:

Skin and eye irritant. Harmful or fatal if swallowed.

FIRST AID:

SKIN: Wash with soap and water. If irritated, seek medical attention.

EYES: Flush with water for 15 minutes. Seek medical attention.

INGESTION: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.

INHALATION: Remove to fresh air. Resuscitate if necessary. Get medical attention.

SPECIAL PRODUCT FEATURES:

Contains No Caustics


Contains No Phosphates

Painted Surface Safe

NFPA

Health

Specific
Hazard



Fire
Hazard

Reactivity
Hazard

HAZARD RATING:

4-EXTREME

3-HIGH

2-MODERATE

1-SLIGHT

Proper Shipping Name: Corrosive Liquids, N.O.S.,
(Ethanolamine), 8, UN 1760, PG III

READ MATERIAL SAFETY DATA SHEET BEFORE USE 05/09