

1010955 - 59011 RM MFD 04/15/11

Contains NO Chlorinated Solvents
(NO 1,1,1-Trichloroethane)

- NO CFC's
- NON-HEXANE
- NON-STAINING
- DRIES FAST
- SAFE ON PLASTIC

FOOD GRADE SILICONE IS HEAT
STABLE FROM -40°F to +285°F

Can be used in the food packaging
and processing industry with
incidental food contact, tables,
conveyors, heat sealing equipment,
slicing equipment.

PREVENTS JAMMING AND
PRODUCTION SLOWDOWN ON
BOTTLING LINES

It can be used on ovens and hoods
to prolong time between cleanings.
Surface should be clean and dry
before coating.

DIRECTIONS: Just spray onto clean,
dry surface and allow about 60
seconds to dry. No need to wipe as
product leaves pure silicone film.



Engineered Chemistries
SUPERIOR SOLUTIONS

GLIDE™

DRY SILICONE SPRAY

FOOD GRADE FOR THE FOOD PACKAGING AND PROCESSING INDUSTRY

NET WT. 11 OZ. (311 Grams)

DANGER:
EXTREMELY FLAMMABLE
VAPOR HARMFUL
CONTENTS UNDER PRESSURE
SEE OTHER CAUTIONS ON SIDE PANEL

REV 04/11

DANGER: Use only in a well ventilated area. Do not use near heat, sparks or open flame. Avoid contact with eyes or prolonged contact with skin. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

KEEP OUT OF REACH OF CHILDREN

CONTAINS:	CAS#
Liquefied Petroleum Gas	68476-86-8
Isoparaffinic Hydrocarbon	64741-66-8
Polydimethylsiloxane	63148-62-9

NFPA

HAZARD RATING:



PROPER SHIPPING NAME:
Consumer Commodity, ORM-D

READ MATERIAL SAFETY DATA SHEET BEFORE USE



To Reorder:
WECHEM, INC.

5734 Susitna Drive, Harahan, LA 70123
LOCAL: (504) 733-1152
FAX: (504) 733-2218
1-800-426-0512
www.wechem.com