

## DESCRIPTION

**HV-500** is a high alkaline stripping compound formulated for heavy-duty industrial use. It removes grease, oil, paint, rust and carbonized soils from a wide variety of steel and iron parts. This high intensity alkaline product contains buffered wetting agents that remain strong and stable under high temperatures over long periods of time. It also contains corrosion inhibitors to prevent flash rusting of parts once they are removed from your tank. Not for use on aluminum or yellow metal parts.

## DIRECTIONS

Average concentration is 6 to 8 ounces of **HV-500** per gallon of water (45 to 60 grams per liter). For de-rusting and paint stripping, use near boiling temperatures, 180° to 212°F. Add compound as needed (**SLOWLY and CAREFULLY**) to avoid boil-over and splashing. Do not air agitate. Use a plastic bristle brush to loosen caked grime and paint. Rinse thoroughly.



Engineered Chemistries  
SUPERIOR SOLUTIONS

# HV-500™

## Hot Vat Compound

**DE-RUSTING ACTION**

**STRIPS OFF PAINT**

**DISSOLVES GREASE**

**BIODEGRADABLE**

**DANGER: CORROSIVE**  
**KEEP OUT OF REACH OF CHILDREN.**  
**FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY.**  
(SEE RIGHT PANEL FOR ADDITIONAL CAUTIONS AND FIRST AID STATEMENTS.)

NET CONTENTS: U.S. GALLON

5/11

## DANGER: CORROSIVE

**Causes severe burns to eyes and skin! Contains sodium hydroxide (caustic soda), which is corrosive.** Do not get in eyes or on skin or clothing. Avoid breathing dust, mist or spray. Do not take internally. Use with adequate ventilation. When handling, wear goggles or face shield, rubber gloves, respiratory protection and protective clothing. Wash thoroughly after handling. Store in a cool, dry place with package tightly sealed. Unrinsed surfaces are slippery when wet. Dispose of in accordance with local, state and Federal regulations.

## FIRST AID

**EYES:** Flush with water for 15 minutes. If irritated, seek medical attention.

**SKIN:** Wash with soap and water. If irritated, seek medical attention.

**INHALATION:** Remove to fresh air. Resuscitate if necessary. Get medical attention.

**INGESTION:** Do not induce vomiting. Rinse mouth. Drink two large glasses of water. Get immediate medical attention.

**CONTAINS:** Sodium Hydroxide.....**CAS #** 1310-73-2

**NFPA**




**HAZARD RATING:**

4-EXTREME  
3-HIGH  
2-MODERATE  
1-SLIGHT

**Proper Shipping Name:** Corrosive Solids, N.O.S. (Contains Sodium Hydroxide Solid), 8, UN 1759, PG II

**READ MATERIAL SAFETY DATA SHEET BEFORE USE.**

**WEICHEM, INC.**  
5734 Susitna Dr  
Harahan, LA 70123  
(504) 733-1152  
800-426-0512  
FAX (504) 733-2218  
[WWW.WEICHEM.COM](http://WWW.WEICHEM.COM)



7 38435 20671 0