



Infinity™

The oil with SPEED!



**Loosens Frozen Metal Parts
Features a 360° Spray Valve**

NET WT: 9.5 OZ.

CAUTION: KEEP OUT OF REACH OF CHILDREN
For industrial and institutional use only.
See side panels for additional CAUTIONS and FIRST AID statements

DESCRIPTION:

INFINITY Penetrating Oil is the ultimate in modern chemistry. It is a combination of high energy polar solvents and other compounds specifically designed to cut through all types of corrosion. INFINITY penetrates, seeps and evaporates into spaces as small as one millionth of an inch and will not attack healthy metal. It saves equipment, time, money and aggravation - and you'll find it's the best penetrating oil you will ever use!

DIRECTIONS:

Point spray nozzle directly and as close as possible to work surface. Saturate surface with sufficient product to thoroughly wet the target area. The attachment of the void injector will enhance the ability to penetrate into tight areas. Required soak time will vary depending on the amount of soil and corrosion present on the surface. Typically, a minute or two is all that is required for most jobs. If the target surface is heavily soiled, use *INFINITY* to preclean before applying the soak application. If extended corrosion protection is required, a light layer of *INFINITY* should be applied to the surface prior to storage.

CAUTION:

DANGER: Flammable when used with void injectors. Keep away from heat, sparks and flame. Use with adequate ventilation. Avoid contact with eyes and prolonged contact with skin. Empty containers may contain explosive vapors. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

FIRST AID:

EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes, while holding upper and lower lids open. Get medical attention immediately. **SKIN CONTACT:** Remove contaminated clothing and shoes. Flush skin with water, followed by washing with soap and water. Get medical attention. **INHALATION:** Remove to fresh air and get medical attention. Provide oxygen if breathing is difficult. Give artificial respiration if breathing stops. **INGESTION: DO NOT INDUCE VOMITING.** Seek medical attention immediately.

CONTAINS:

| | CAS# |
|----------------------------------------|------------|
| Petroleum Base Oil | 64742-46-7 |
| Aliphatic Petroleum Distillate | 78-92-2 |
| Petroleum Solvent | 64742-95-6 |
| Dipropylene Glycol Methyl Ether | 34590-94-8 |
| Hydrocarbon Solvent | 123-42-2 |
| Petroleum Naphtha | 64742-47-8 |
| Terpene Alcohols and Hydrocarbon | 8002-09-3 |
| Hydrocarbon Propellent | 68476-86-8 |

NFPA



HAZARD RATING:

4-EXTREME
3-HIGH
2-MODERATE
1-SLIGHT
0-INSIGNIFICANT

DOT PROPER SHIPPING NAME:
Consumer Commodity, ORM-D

READ MATERIAL SAFETY DATA SHEET BEFORE USE

To Reorder:
WEICHEM, INC.
5734 Susitna Drive, Harahan, LA 70123
LOCAL: (504) 733-1152
FAX: (504) 733-2218
1-800-426-0512
www.wechem.com