

Met-All N2600 Premium Nickel Antiseize combines nickel and graphite in a premium grade aluminum complex grease which provides excellent protection without the use of copper or lead. Temperature-resistant to 2600° F. This antiseize provides our strongest chemical resistance. Its spray pattern is smooth and precise.

SUGGESTED APPLICATIONS:


Threaded connections, chemical-resistant fittings, flanges, and special alloy metals, including stainless steel. Many applications exist in oil refineries, waste and water treatment plants, and chemical plants.

DIRECTIONS:

Shake until mixing balls rattle freely inside. Hold can upright. Spray parts liberally before assembly to lubricate and protect. For pinpoint application or to get into holes or other hard-to-reach areas, firmly insert extension tube into hole in spray button.

PRECAUTIONS:

Use outdoors or in a well-ventilated area with a constant, abundant supply of fresh air. Do not allow product vapor to accumulate. Avoid breathing product mist and vapor. Excessive inhalation of vapor, intentional misuse by concentrating and inhaling vapor, or ingestion of liquid may be harmful or fatal. Overexposure may cause damage to nervous system, digestive and respiratory tracts (including lungs), and other organs. Do not get in eyes. Avoid getting on skin. Possible skin and eye irritant.



Met-All N2600™

Premium Nickel Anti-Seize

- Protects Against Seizing and Galling
- Temperature-Resistant to 2600°F
- Eases Assembly and Disassembly of Metal Parts
- Meets MIL-A-907-E
- Acid-Resistant

EXTREMELY FLAMMABLE:
KEEP OUT OF REACH OF CHILDREN
NOT FOR USE ON OXYGEN SYSTEMS
FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY.

(SEE RIGHT PANEL FOR ADDITIONAL CAUTIONS AND FIRST AID STATEMENTS.)

To Reorder:
WECHEM, INC.
5734 Susitna Drive , Harahan, LA 70123
(504) 733-1152 * 1-800-426-0512
FAX: (504) 733-2218
www.wechem.com

Net wt.13 oz.(369 grams)

Product contains extremely flammable gas and liquid under pressure. Vapor, liquid, and freshly-applied product may burn or explode if ignited. Do not use near sources of heat or ignition (including flames, sparks, and glowing-hot surfaces). Cans that touch live electrical circuits may arc, melt, burst, burn, and explode. Vapor is heavier than air and may become concentrated to hazardous levels in low areas. Store in a cool, dry, well-ventilated area out of direct sunlight. Do not expose to heat or store at temperatures above 120°F. Do not puncture or burn can. Use and dispose of product in accordance with all applicable federal, state, and local law and regulations.

WARNING:

This product contains a chemical known to the State of California to cause cancer.

FIRST AID:


EYES: Flush with water for 15 minutes. Seek medical attention.

SKIN: Wash with soap and water. If irritated, seek medical attention.

INHALATION: Remove to fresh air. Resuscitate if necessary. Get medical attention.

INGESTION: Do not induce vomiting. Get immediate medical attention.

CONTAINS:	CAS#
Heptane	142-82-5
Nickel Flake	7440-02-0
Petroleum Oil	64742-65-0
Graphite	7782-42-5
Propane	74-98-6
Butane	106-97-8

NFPA		Fire Hazard HAZARD RATING: 4-EXTREME 3-HIGH 2-MODERATE 1-SLIGHT
Health Specific Hazard	Reactivity Hazard	

Proper Shipping Name: Consumer Commodity, ORM-D

READ MATERIAL SAFETY DATA SHEET BEFORE USE