

Provides a one-step solution to battery terminal corrosion removal and acid neutralization. Delivers a powerful, heavy duty foam that clings to battery surfaces, provides extended contact time and neutralizes acid quickly. Helps eliminate power leaks and aids in restoring full starting power.

Features a low odor, non-flammable, water-soluble formula. Contains a unique color indicator that changes from yellow to red as battery acid is neutralized.

Leaves behind a residual film that provides short-term corrosion resistance.

FOR USE ON:

Fleet Cars, Trucks and Buses, Taxi Fleets, Forklifts, Construction, Agricultural and Marine Equipment, Aircraft, Golf Carts, Postal Vehicles, Industrial Battery Backup Systems.

DIRECTIONS:

SHAKE WELL BEFORE USING

Spray on cables, clamps, terminals, brackets, housings and entire battery surface. (Be sure cell covers are tightly sealed). Product will spray out light yellow and turn red in the presence of acid. Allow foam to work for several minutes, then flush off with water. Follow with a second application. If solution still turns red, acid neutralization process is not complete. Allow to set then repeat. For heavy deposits, agitation with a wire brush may be needed. If sprayed foam remains yellow, all acid has been neutralized. Allow product to dry and form residual protective film.



Engineered Chemistries
SUPERIOR SOLUTIONS

Neutralizer

BATTERY TERMINAL CLEANER

EXTENDS BATTERY LIFE

NON-FLAMMABLE

INCREASES POWER OUTPUT

INCLUDES

COLOR PERFORMANCE

INDICATOR

NET WT. 18 OZ. (1 LB. 2 OZ.)
(510 GRAMS)

CAUTION:
CONTENTS UNDER PRESSURE
SEE OTHER CAUTIONS ON SIDE PANEL

REV 03/11

CAUTION: Do not puncture or incinerate container. Do not expose to heat, sparks or open flame. Do not store at temperatures above 120°F.

FIRST AID: IF EYE CONTACT: Flush with large amount of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

KEEP OUT OF REACH OF CHILDREN

CONTAINS:	CAS#
Liquefied Petroleum Gas..	68476-86-8
Ethylene Glycol	
Monobutyl Ether	111-76-2

NFPA	HAZARD RATING:
Health	Flammability 4-EXTREME 3-HIGH 2-MODERATE 1-SLIGHT 0-INSIGNIFICANT
1	
0	
0	
Special Hazard	Reactivity

PROPER SHIPPING NAME:
Consumer Commodity, ORM-D

READ MATERIAL SAFETY DATA SHEET BEFORE USE



To Reorder:
WECHEM, INC.
5734 Susitna Drive • Harahan, LA 70123
LOCAL: (504) 733-1152
FAX: (504) 733-2218
1-800-426-0512
www.wechem.com