

DESCRIPTION:

Poly D is specifically formulated to counteract problems associated with the use of waste water and water treatment polymers. It is ideally suited for use as an anti-blinding agent in de-watering belt press operations. The continuous injection of **Poly D** at Wechem's recommended dosages will end belt blinding, increase porosity, increase process efficiency and produce drier sludge cakes. It may also be used to disperse polymer residues in polymer tanks, polymer lines, cooling towers and spill areas.

This product is neutral in pH and contains NONE of the following ingredients:

Caustic Salts	Solvents
Sodium Metasilicate	Mineral Acids
Ammonia	Sodium Carbonate

DIRECTIONS:

For Polymer Spills: Using low pressure sprayer or hose & nozzle assembly, apply to polymer spills. Let sit 15 to 30 minutes. Spray off using high pressure sprayer.

For Belt Wash Systems: Inject **Poly D** into system using a suitable chemical injection metering pump. A working dosage of 1 gallon **Poly D** up to 32,000 gallons of wash water is recommended.

UNIT OF MEASURE: U.S. GALLONS



POLY D™

Polymer Dispersant & Belt Wash Anti-Blinding System

**KEEP OUT OF REACH OF CHILDREN.
FOR INDUSTRIAL AND INSTITUTIONAL USE
ONLY.**

(SEE RIGHT PANEL FOR ADDITIONAL CAUTIONS AND FIRST AID STATEMENTS.)

WECHEM, INC.

5734 Susitna Drive Harahan, LA 70123
PHONE: (504) 733-1152 * 1-800-426-0512
FAX: (504) 733-2218 * www.wechem.com


1099

FIRST AID:

EYES: Flush with water for fifteen minutes. If irritated, seek medical attention.

SKIN: Wash with lukewarm water. If irritated, seek medical attention.

INGESTION: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.

NFPA		HAZARD RATING:
Health	0	4-EXTREME
Specific Hazard	0	3-HIGH
	0	2-MODERATE
		1-SLIGHT

Proper Shipping Name:
Cleaning Compounds, Liquid N.O.I.

READ MATERIAL SAFETY DATA SHEET BEFORE USE