

## USE ON

MARINE EQUIPMENT

UNDERCOATING

STORAGE OF TOOLS & DRILLS

FARM & ROAD MACHINERY

FINISHED OR FABRICATED CASTINGS

VALVES

STAMPINGS

*Complies with MIL-C-16173D-Grade 4 and MIL-C-83933A*

### DESCRIPTION

PROTECTO FLEX is a long term, flexible, non-tacky, dust-resistant coating that will not crack, peel, flake or check over a wide temperature range (-40°F TO 175°F).

PROTECTO FLEX leaves a translucent film that allows protected parts to be seen.

PROTECTO FLEX can be flushed off easily with mineral spirits whereas other coatings are difficult to remove and usually require special solvents.

### DIRECTIONS

Make sure surface is clean and dry. Apply a thin uniform coating. Allow approximately 5 minutes to set up. For more severe storage conditions, a second coating can be applied within a few minutes. Complete setting of protective coating takes approximately two hours after application.



# PROTECTO FLEX™

## METAL PARTS PROTECTOR

- LONG TERM CORROSIVE PREVENTATIVE
- FLEXIBLE DUST RETARDANT COATING

See through film allows parts to be indentified.

**CAUTION: CORROSIVE  
HARMFUL IF SWALLOWED  
KEEP OUT OF REACH OF CHILDREN.  
FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY.**  
(SEE RIGHT PANEL FOR ADDITIONAL CAUTIONS AND FIRST AID STATEMENTS.)

**NET CONTENTS: U.S. GALLON**

### CAUTION

Use only in well-ventilated areas. Avoid contact with eyes or prolonged contact with skin. Do not expose to heat or store at temperatures above 120°F.

### FIRST AID


**EYES** - Flush with water for 15 minutes. If irritated, seek medical attention.

**SKIN** - Wash with soap and water. If irritated, seek medical attention.

**INHALATION** - Remove to fresh air. Resuscitate if necessary. Seek medical attention.

**INGESTION** - Do not induce vomiting. Get medical attention.

CONTAINS:	CAS#
Aliphatic Petroleum Distillates.....	64742-88-7
Aliphatic Hydrocarbon.....	8052-41-3
Calcium Slat of Oxidized Petrolatum.....	68425-34-3

NFPA	HAZARD RATING:
	4-EXTREME 3-HIGH 2-MODERATE 1-SLIGHT 0-INSIGNIFICANT

READ MATERIAL SAFETY DATA SHEET BEFORE USE.

WEICHEM, INC.  
5734 Susitna Dr.  
Harahan, LA 70123  
504.733.1152  
800.426.0512  
FAX 504.733.2218  
www.wechem.com

