

No Chlorinated Solvents

(No 1,1,1-Trichloroethane)

PROTECTO FLEX is a long-term, flexible, non-tacky dust-resistant coating that will not crack, peel, flake or check over a wide temperature range — (-40°F to 175°F).

PROTECTO FLEX provides a translucent coating which allows identification codes underneath to be easily read.

PROTECTO FLEX can be flushed off easily with mineral spirits whereas other coatings are difficult to remove and usually require special solvents.

USE ON:

Large molds, offshore drilling parts, outdoor airport ground handling equipment, castings, metal parts in transit, metal parts and bearings in ocean transport, seasonal equipment in storage.

DIRECTIONS:

Make sure surface is clean and dry. Spray a thin uniform film. Allow approximately 5 minutes to set up. For more severe storage conditions, a second coating can be applied within a few minutes. Complete setting of protective coating takes approximately two hours after spraying.



LONG TERM METAL PARTS PROTECTOR

NON-CHLORINATED CORROSION

PREVENTATIVE

FLEXIBLE DUST

RETARDANT COATING

SEE-THROUGH FILM

ALLOWS PARTS TO BE IDENTIFIED

EASILY APPLIED AND REMOVED

NET WT. 14 OZ.
(396 Grams)

DANGER:
EXTREMELY FLAMMABLE
HARMFUL OR FATAL IF SWALLOWED
CONTENTS UNDER PRESSURE
SEE OTHER CAUTIONS ON SIDE PANEL

5-06

DANGER:

Use only in a well-ventilated area. Do not use near heat, sparks or open flame. Avoid contact with eyes or prolonged contact with skin. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

FIRST AID:

IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

IF SKIN CONTACT: Wash with soap and water. If irritation persists seek medical attention.

EXCESSIVE INHALATION: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

IF INGESTED: Do not induce vomiting. Seek medical attention immediately.

KEEP OUT OF REACH OF CHILDREN

CONTAINS:	CAS#
Liquified Petroleum Gas.....	68476-85-7
Mineral Spirits	8052-41-3
Isoparaffinic Hydrocarbon	64741-66-8

NFPA	HAZARD RATING:
	4-EXTREME 3-HIGH 2-MODERATE 1-SLIGHT 0-INSIGNIFICANT

PROPER SHIPPING NAME:
Consumer Commodity, ORM-D

READ MATERIAL SAFETY DATA SHEET BEFORE USE

To Reorder:
WECEM, INC.
5734 Susitna Drive • Harahan, LA 70123
LOCAL: (504) 733-1152
FAX: (504) 733-2218
1-800-426-0512
www.wechem.com

1010955 - 72214