

USE ON:

Porous & Uneven Surfaces
Cardboard · Leather
Most Plastics · Paper &
Acrylic Labels.

Recommended for adhering decorative laminate to particleboard and MDF (medium-density fiberboard) substrates, metals and plywood. Adjustable tip provides a webbing type spray pattern that is water white and does not contain Methylene Chloride. Its unique formula prevents soak-in of the adhesive on porous surfaces. It offers the user very high coverage with a fast tack time for general purpose bonding of a wide variety of substrates. Provides both temporary and permanent bonds.

DIRECTIONS

SHAKE WELL BEFORE USING. Bonding surfaces must be free from dust and debris. For best results, use at temperatures above 50°F (10°C). Spray from a distance of 8-10 inches, keeping the tip moving in order to get an even webbing of adhesive on the surface to be bonded. If a permanent bonding is desired, spray both surfaces, allow adhesive to dry to a tack and then bond.

CLEANING SPRAY TIP

When finished with application, always turn can upside down and spray for two seconds to clear valve and prevent clogging. If adhesive accumulates around nozzle, wipe clear while wet. If dried in valve opening, remove with degreasing solvent. Not recommended for unsupported vinyl fabric. Certain plastic and elastomeric substrates can exhibit bond failure due to plasticizer migration. Combinations of high temperature and humidity can promote bond failure. Testing of production parts in typical operating environments for compatibility is recommended. Excess adhesive or over-spray can be cleaned up with a petroleum solvent.



Engineered Chemistries
SUPERIOR SOLUTIONS

STICK IT™

Heavy-Duty Adhesive Spray

- ★ **WIDE WEB SPRAY PATTERN**
- ★ **HIGH SOLIDS**
- ★ **WATER PROOF BOND**
- ★ **NO CHLORINATED SOLVENTS**

DANGER: EXTREMELY FLAMMABLE. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. MAY CAUSE SKIN, EYE AND RESPIRATORY IRRITATION. CONTENTS UNDER PRESSURE. READ CAUTIONS ON RIGHT SIDE PANEL.

KEEP OUT OF REACH OF CHILDREN.



NET WT. 12 OZ. (340 GRAMS)

DANGER: Extremely flammable liquid and vapor. Vapor harmful. Use with adequate ventilation. Avoid breathing vapors, mist or spray. Causes eye irritation and/or skin irritation. Contents under pressure and can explode if exposed to flame, heat or ignition source. May cause flash fire. Keep product away from heat, sparks, flames and sources of static discharge. Do not store above 120°F (49°C) or in direct sunlight. Do not puncture, incinerate or discard in compactor.

NOTE: Use as directed. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Primary health concerns regarding this product are related to the solvent vapors.

FIRST AID

EYES - Flush with large amount of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists, get medical attention immediately.

SKIN - Wash with plenty of soap and water. If irritation persists, seek medical attention.

INHALATION - Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

INGESTED - Do not induce vomiting. Seek medical attention immediately.

CONTAINS	CAS#
2-Propanone.....	67-64-1
Hexane.....	110-54-3
Cyclohexane.....	110-82-7
Liquefied Petroleum Gas.....	68476-86-8

NFPA	HAZARD RATING:
Health	4-EXTREME
Flammability	3-HIGH
Special Hazard	2-MODERATE
Reactivity	1-SLIGHT
	0-INSIGNIFICANT

READ MATERIAL SAFETY DATA SHEET BEFORE USE.

WECHEM, INC
5734 Susitna Dr.
Harahan, LA 70123
504.733.1152
800.426.0512
FAX 504.733.2218
www.wechem.com

