

### DESCRIPTION

Our multi-grade **Super G 85w140** Gear Oil is specially formulated to meet year-round lubricant requirements. This product replaces single weight gear oils and functions under wide temperature extremes. It flows freely as an SAE 85 in cold temperatures, yet at high temperatures it maintains the viscosity of an SAE 140, assuring full film protection. This gear oil is made from premium quality paraffin base stocks especially for heavy duty requirements. It is designed to withstand the most severe shock loads. Special adhesive and cohesive additives are blended into this product to maintain a continuous heavy film of oil and provide maximum protection. May be used in virtually all types of enclosed gears.

### PERFORMANCE CHARACTERISTICS

**Meets and/or Exceeds:** MIL-L-2105E; API GL2-GL5; API PG 2, MTL, CRC L-33 Moisture and Corrosion Test; CRC L-37 High Torque Axle Test; CRC L-42 High Speed Axle Test; ASTM D-892 Foam Test; ASTM D-130 Copper Corrosion Test; Mack GO-J; John Deere J11 D; ICH B-22; Clark MS-8; Terex EEMS 19003; White Motors MS 0016; Ford M2 C105A; Ford M2C108C; GM Spec. No. 9985044 and No. 9985182; Chrysler MS 3636; Chrysler MS 3725. All equipment manufacturers specifying the use of MIL-L-2105C or MIL-L-2105D type lubricant or equivalent.

### USES

The SAE weight selected for a particular type of equipment should correspond with the recommended weight and temperature recommendations in the owners manual or current check chart. Recommended as a service fill of axles, manual transmissions, transfer cases & power dividers, differentials, all heavy duty hypoid and spiral bevel axles, all automotive and industrial worm gears, and particularly on conventional axles using phosphate treated gears.

**UNIT OF MEASURE: U.S. GALLONS**



# SUPER G™

## SAE 85W140

### Multi-Viscosity Extreme Pressure Gear Oil

*The Oil That Climbs*

- ◆ *Extends Oil Life*
- ◆ *Reduces Operating Temperatures*
- ◆ *Reduces Wear and Gear Scoring*

### WARNING:

**KEEP OUT OF REACH OF CHILDREN.**

**FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY.**

(SEE RIGHT PANEL FOR ADDITIONAL CAUTIONS AND FIRST AID STATEMENTS.)

To Reorder:  
**WECHEM, INC.**

5734 Susitna Drive Harahan, LA 70123

(504) 733-1152 \* 1-800-426-0512

3/08

### CAUTION:

Do not ingest. If this should occur, drink large volumes of water and seek medical attention. Avoid storage of product in freezing temperatures. Keep container sealed when not in use. Rinse empty container before discarding in an authorized landfill site. **KEEP OUT OF REACH OF CHILDREN.**

### FIRSTAID:

**EYES:** Wash with large amounts of water. If irritation persists, call a physician.  
**SKIN:** Remove contaminated clothing. Wash with soap and water.  
**INHALATION:** Remove to fresh air.  
**INGESTION:** DO NOT INDUCE VOMITING. Give 3-4 glasses of water. Seek medical attention.

READ MATERIAL SAFETY DATA SHEET BEFORE USE

CONTAINS:	CAS #
Petroleum Oil Mixture.....	8002-05-9
Polymer.....	9003-29-6
N.J.....	800962-5003P
N.J.....	800962-5019P
N.J.....	800962-5008P

NFPA	HAZARD RATING:
	4-EXTREME 3-HIGH 2-MODERATE 1-SLIGHT
<b>DOT NAME:</b> Petroleum Oils, Greases	