

WECHEM®

SUPER SEAL™

WHITE RTV SILICONE RUBBER ADHESIVE/SEALANT

- 100% Silicone Rubber
- Remains Flexible
- -60°F to 500°F

- Easy Application
- No Caulking Gun Required
- Multi-Purpose
- Automotive/Industrial

**WARNING! OUTER CONTAINER
IS PRESSURIZED WITH A FLAMMABLE
HYDROCARBON PROPELLANT.
DO NOT REMOVE RUBBER PLUG ON BOTTOM
OF CAN.
CONTENTS UNDER PRESSURE. DIRECT
CONTACT WITH UNCURED SEALANT
IRRITATES EYES AND SKIN.
Before using, carefully read caution elsewhere on label.**

NET WT. 8 OZ. (226 g)

SUPER SEAL is a high quality Silicone Sealant which can be dispensed directly from the can. It is the perfect choice for exterior and interior sealing and caulking. It bonds to metal, glass, marble, tile, ceramics, porcelain, painted surfaces, non-oily woods, plastic, and rubber. Use it for all your sealing and caulking needs. It is a great adhesive for bonding surfaces together. Conventional paints will not adhere. Paint first, then seal.

TEMPERATURE RANGE: -60°F to 500°F

DIRECTIONS:

1. Clean and dry surfaces. Remove dirt, grease, and old caulk.
2. Depress either side of the nozzle.
3. Apply silicone and tool within 10 minutes. Allow 24 hours for full cure and maximum strength.
4. After use, form bead of silicone over end of nozzle. Cured plug can be removed for next use.

SPECIFICATIONS: Meets USDA, F.D.A. reg #21, CFR 177.2600, TT-S-001543A (COM-NBS) Class A, MIL-A-46106B Amend 3, Type 1. Meets criteria specified by UL and NSF.

TYPICAL USES:

Gasketing: Pump-Oil Pans; Valve Covers; Gear Boxes; Compressors

CAUTION: ON CONTACT, UNCURED SEALANT CAUSES IRRITATION.

Avoid contact with eyes and skin. Contact lens wearers take appropriate precautions. IN CASE OF CONTACT, flush eyes with water. Call a physician. Remove from skin with a dry cloth or paper towel. Sealant releases acetic acid (vinegar-like odor) during cure. May cause drowsiness. Contents under pressure. Do not puncture or incinerate. Do not store at temperatures above 120°F.

CONTAINS:		CAS#
Methyltriacetoxysilane		4253-34-3
Silica, Amorphous		7631869
Ethyltriacetoxysilane		17689-77-9
NFPA		HAZARD RATING:
Health 1	1 Flammability	4-EXTREME
Special Hazard	0 Reactivity	3-HIGH
		2-MODERATE
		1-SLIGHT
		0-INSIGNIFICANT
Proper Shipping Name: Consumer Commodity, ORM-D		

**READ MATERIAL SAFETY DATA SHEET BEFORE USE
KEEP OUT OF REACH OF CHILDREN**

To Reorder: WEICHEM, INC.
5734 Susitna Drive, Harahan, LA 70123
(504) 733-1152 * FAX: (504) 733-2218
1-800-426-0512 * www.wechem.com

85470

5/07