

DESCRIPTION: TF LUBE is a chemically inert, non-oily, fast-drying lubricant and release agent made with an extremely fine polytetrafluoroethylene powder.

TF LUBE features outstanding microscopic film-forming properties and resists temperatures from -100°F to +500°F. An odorless, stainless coating that is more slippery than silicone, graphite or oil. TF LUBE is excellent for reducing low speed friction.

The dry film is not affected by most chemicals and when used as a release agent, allows parts to be painted without cleaning.

DIRECTIONS: Shake can vigorously, rattling agitator ball for a minimum of 1 full minute. Surface to be treated must be clean and dry. Hold container 5 to 10 inches from surface and spray a thin film over area.

- DRIES QUICKLY
- CAN BE REMOVED WITH TOLUENE
- WILL NOT ATTRACT DUST
- CLEAN & NON-OILY



TF LUBE™

DRY LUBRICANT & RELEASE AGENT with PTFE

**NON-CHLORINATED
NON-HEXANE
CHEMICALLY INERT**



REV 01-10

NET WT. 10 OZ. (283 Grams)

**DANGER: EXTREMELY FLAMMABLE.
VAPOR HARMFUL. CONTENTS UNDER PRESSURE.
SEE OTHER CAUTIONS ON BACK PANEL.**

DANGER: Use only in a well ventilated area. Do not use near heat, sparks or open flame. Avoid contact with eyes or prolonged contact with skin. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately. IF SKIN CONTACT: Wash with soap and water. If irritation persists seek medical attention. EXCESSIVE INHALATION: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. IF INGESTED: Do not induce vomiting. Seek medical attention immediately.

KEEP OUT OF REACH OF CHILDREN

CONTAINS:	CAS#
Liquefied Petroleum Gas	68476-86-8
Isoparaffinic Hydrocarbon.....	64741-66-8
Heptane, Branched, Cyclic, and Linear	426260-76-6
Isopropyl Alcohol.....	67-63-0
Polytetrafluoroethylene.....	9002-84-0

NFPA

Health
Special Hazard

1
4
0

Flammability
Reactivity

4-EXTREME
3-HIGH
2-MODERATE
1-SLIGHT
0-INSIGNIFICANT

HAZARD RATING:

PROPER SHIPPING NAME:
Consumer Commodity, ORM-D

READ MATERIAL SAFETY DATA SHEET BEFORE USE

To Reorder:

WECHEM, INC.

5734 Susitna Drive, Harahan, LA 70123

LOCAL: (504) 733-1152

FAX: (504) 733-2218

1-800-426-0512

www.wechem.com

NOTE:

Color proofs are provided **ONLY** as a visual reference to the final piece.

The colors shown are **ONLY** representational and are **not intended** to match the actual press or silk screening colors.

customer / product no.

1010955 - 81010

FINISHING CODE

P 0-99-0



FINISHING

- One Color Silk Screen
 Two Color Silk Screen
 Paper Label
 Litho-Like Label
 Lithograph Can
 Process Spot

LABEL PROOF APPROVAL Your Approval of This Label is Our Authority to Proceed.

OK PROOF APPROVED

PLEASE SUBMIT ANOTHER PROOF

CPC WILL NOT PROCEED WITHOUT A SIGNED APPROVAL.

original: 01/06/10

revision: _____

art by: michajljszyn

Signature _____

Date _____