

**NON-CHLORINATED • NON-FLAMMABLE
NON-CONDUCTIVE**

MEETS MIL-C161730 GRADE 3 AND MIL C-23411

**NO Chlorinated Solvents
(NO 1,1,1-Trichloroethane)
(NO Perchloroethylene)
(NO Methylene Chloride)**

HIGH DIELECTRIC STRENGTH

NUT and BOLT LOOSENER — Rapidly penetrates through rust and corrosion.

WATER DISPLACER — Displaces moisture from electrical parts. Prevents malfunction to electrical equipment exposed to high humidity.

LUBRICANT — Assures free and easy movement of parts.

ANTI-CORROSIVE COATING — Leaves a protective film that seals out future rust, corrosion and the harmful effects of moisture.

USES: Motors, relays, switches, plugs, reostats, electronic and electrical assemblies, parking and water meters, marine equipment, vending machines, vehicles, appliances, tools, machinery, generators, batteries, chargers, jigs, fixtures, fans, battery terminals, motorcycles, blowers, hoists, overhead doors.

DIRECTIONS:

1. For best performance and fullest protection, first clean object with degreaser solvent to remove grease, oil and debris. This will prevent material from becoming contaminated, especially when used in a dip tank.
2. Apply as a spray, brush on, or use in a dip tank.
3. Allow wetted-out rusted parts to be immersed in solution for several minutes.
4. Always keep container closed to prevent evaporation or contamination.



TRIO™

Multi-Use Mechanical Spray

**Penetrates
Lubricates
Demoisturizes
Leaves Rust
Preventative Film**

NET CONTENTS: 5 GALLONS

**CAUTION: VAPOR HARMFUL
CONTENTS UNDER PRESSURE
SEE OTHER CAUTIONS ON BACK PANEL**



CAUTION: Use only in a well-ventilated area. Contents under pressure. Do not puncture or incinerate container. Avoid contact with eyes or prolonged contact with skin. Avoid contamination of food. Do not expose to heat or store at temperatures above 120°F.

FIRST AID:

IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists seek medical attention.

IF SKIN CONTACT: Wash with soap and water. If irritation persists seek medical attention.

EXCESSIVE INHALATION: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

IF INGESTED: Do not induce vomiting. Seek medical attention immediately.

CONTAINS:

CAS#

Mineral Oil.....	8042-47-5
Octamethylcyclotetrasiloxane.....	556-67-2
Decamethylcyclopentasiloxane.....	541-02-6
Dipropylene Glycol Monomethyl Ether....	34590-94-8

NFPA

HAZARD RATING:



**DOT NAME:
Consumer Commodity, ORM-D**

READ MATERIAL SAFETY DATA SHEET BEFORE USE

To Reorder:

WECHEM, INC.

5734 Susitna Drive, Harahan, LA 70123

LOCAL: (504) 733-1152

FAX: (504) 733-2218

1-800-426-0512

www.wechem.com