

**Thread Seal** is a premium Teflon® enhanced compound which provides superior sealing for most threaded metal or plastic pipe. **Thread Seal** will prevent leaks and seal most common fluids and gases, including fuels, oils, water, refrigerants, steam and inert gases. Non-hardening formula will not crack, shred or contaminate most systems. Eases assembly and disassembly of metal and plastic fittings.

**Thread Seal** will not damage most plastic fittings. Seals to bursting pressure of pipe and is rated to 10,000 psi.

#### SUGGESTED APPLICATIONS

Plumbers "pipe dope" replaces Teflon® tape, HVAC preferred. Use Teflon® sealant on pipe threaded joints 1/4" and larger. Temperature rating of -30°F to 500°F.

#### DIRECTIONS

Always refer to Material Safety Data Sheet (MSDS) and precautions on right side panel for safety information.

1. Clean and dry pipe threads.
2. Apply Thread Seal onto male threads with stiff bristle brush.
3. Assembly parts.
4. To avoid contamination, close container when not using.



Engineered Chemistries  
SUPERIOR SOLUTIONS



# Thread Seal™

## Pipe Sealing Paste with PTFE



- SOLVENT - FREE
- NON-SHRINKING
- PREVENTS GALLING & CORROSION
- SEAL MOST FLUIDS & GASES
- LUBRICATES
- ACID - RESISTANT
- FOR USE WITH ALL METALS & PLASTIC THREAD PIPES

### CAUTION

**KEEP OUT OF REACH OF CHILDREN**  
FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY.  
(SEE RIGHT PANEL FOR ADDITIONAL CAUTIONS AND FIRST AID STATEMENTS.)

NET WT 8 OZ (227G)

5/11


**CAUTION:** Possible eye and skin irritant. If eye contact should occur, flush area immediately with water and get prompt medical attention. Clean affected skin with mineral spirits, then with soap and water. SEEK MEDICAL ATTENTION if ingested or if any irritation persist.

#### FIRST AID

**EYES:** Immediately flush eyes with plenty of water. Get medical attention if irritation persists.

**SKIN:** Wash with soap and water. If irritated seek medical attention.

**INGESTION:** Do not induce vomiting. Drink a large glass of water or milk. Get immediate medical attention.



READ MATERIAL SAFETY DATA SHEET BEFORE USE.

WEICHEM, INC.  
5734 Susitna Dr.  
Harahan, LA 70123  
504.733.1152  
1.800.426.0512  
FAX 504.733.2218  
www.wechem.com



7 38435 20551 5