

- SAFE ON PLASTICS • NON-FLAMMABLE SPRAY
- NO CHLORINATED SOLVENTS
- NON-CONDUCTIVE • OZONE FRIENDLY
- NEVER-DRY COATING



TRIO®

Multi-Use Mechanical Spray

TRIO® penetrates through rust and scale to loosen parts which have been frozen by corrosion and lubricates parts to ensure free and easy movement. TRIO® demoiaturizes and creates a waterproof film that dries out electrical equipment, inhibits corrosion and prevents electrical discharge. Lastly, it protects and creates a non-drying film that seals parts against atmospheric and mild chemical corrosion.

DIRECTIONS:

To Remove Corrosion: Spray liberally directly onto dirt and scale. Allow to penetrate. Remove loosened scale, then reapply to leave an anti-corrosion coating.

To Displace Moisture: Spray electrical equipment and other surfaces until thoroughly saturated. Allow to penetrate before attempting to restart, then reapply to protect surfaces.

To Loosen Frozen Nuts and Bolts: Apply liberally to frozen nuts and bolts, hinges and sliding and rotating parts. Allow to penetrate into threads. Work back and forth, then reapply to leave a never-dry, protective lubricating film.

To ensure adequate protection, reapply periodically.

IDEAL FOR USE ON:

- Locks / Hinges
- Nuts / Bolts
- Tools
- Rods / Reels
- Distributors
- Wet Engine
- Electrical Contacts
- Guns
- Sockets
- Electrical Motors
- Breakers
- Batteries
- Rollers

**Penetrates
Lubricates
Demoisturizes
Leaves Rust
Preventative Film
39,000 Volt
Dielectric Strength**

NET WT. 12 OZ. (340 Grams)

**CAUTION: VAPOR HARMFUL.
CONTENTS UNDER PRESSURE.
KEEP AWAY FROM CHILDREN.**

For industrial and institutional use only. See right panel for additional cautions and First Aid statements.

CAUTION: Use only in a well ventilated area. Contents under pressure. Do not puncture or incinerate container. Avoid contact with eyes or prolonged contact with skin. Avoid contamination of food. Do not expose to heat or store at temperatures above 120°F.

FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists seek medical attention. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

CONTAINS:	CAS#
Mineral Oil	8042-47-5
Octamethylcyclotetrasiloxane	556-67-2
Decamethylcyclopentasiloxane	541-02-6
Dipropylene Glycol Monomethyl Ether	34590-94-8
Carbon Dioxide	124-38-9

NFPA

HAZARD RATING:



DOT NAME:
Consumer Commodity, ORM-D

READ MATERIAL SAFETY DATA SHEET BEFORE USE



**To Reorder:
WECHEM, INC.
5734 Susitna Drive, Harahan, LA 70123
LOCAL: (504) 733-1152
FAX: (504) 733-2218
1-800-426-0512
www.wechem.com**