

*One Step Seal & Finish · Exceptionally Long Wearing · Non-Yellowing
Slip & Scuff Resistant · Super High Density · Highly Resistant to Soil*

SLIP RESISTANCE (ASTM D2047) SOIL RESISTANCE (ASTM D3206)
RECOATABILITY (ASTM D3153) REMOVABILITY (ASTM D1792)
DETERGENT RESISTANCE (ASTM D3207)

DESCRIPTION:

ULTRA GLOSS is a remarkable new metal cross linked floor finish. This complete product seals and finishes in one easy step. Especially suited for non-resilient floors, this product excels with use on terrazzo, quarry tile, brick, slate, Mexican tile, concrete and other floors. **ULTRA GLOSS** is also perfect for use on all resilient floors, including: asphalt tile, ceramic tile, linoleum, rubber, sealed wood, vinyl and vinyl asbestos tile.

DIRECTIONS:

Floor Preparations: Strip floor of old finish and wax, paying particular attention to baseboards, corners, under furniture, and built up areas. Rinse thoroughly and allow to dry.

Application: Using a clean mop or applicator, apply a thin uniform coat of finish. Avoid excessive agitation and do not allow material to dry in puddles. Apply 3 to 5 coats. Make sure finish is completely dry before applying additional coats.

Spray Buff: To restore original luster, spray buff with an approved formula.

High Speed Burnishing: This is an ideal product for use with a high speed burnishing machine of 1000 RPM or higher. The floor should be damp mopped with a suitable neutral cleaner and allowed to dry. The surface may then, as desired, be dry burnished with a high speed white or tan buffing pad, or using the same equipment, be spray buffed using **Buff-N-Shine**. An alternative method of insuring a long lasting durable surface, would be to apply **Revive** mop-on restorer, allow to dry and then follow the dry buffing procedure.

Maintenance: Maintain in the conventional manner by cleaning with a treated yarn dust mop to remove surface dirt daily. Damp mop or clean with an automatic scrubber as required, using an approved neutral cleaner at the specified dilution. Spray buffing to remove embedded soils is recommended. Worn areas, or the entire floor, may be recoated as required to maintain a uniform high gloss. When stripping becomes necessary, use **MOP OFF** according to label directions.



ULTRA GLOSS™

“Wet Look” Floor Finish High Speed Burnishing



CAUTION
KEEP OUT OF REACH OF CHILDREN

FOR INDUSTRIAL AND INSTITUTIONAL USE ONLY.
(SEE RIGHT PANEL FOR ADDITIONAL CAUTIONS AND FIRST AID STATEMENTS.)

CAUTION:

May be harmful if taken internally. Avoid contact with eyes. In case of contact, flush eyes with water for 15 minutes. Consult physician immediately. Keep from freezing.

FIRST AID:

EYES: Flush with water for 15 minutes. Seek medical attention.

SKIN: Wash with soap and water. If irritated, seek medical attention.

INHALATION: Remove to fresh air. Resuscitate if necessary. Get medical attention.

INGESTION: Induce vomiting. Get immediate medical attention.

CONTAINS:	CAS #
DEG Ethyl Ether	111-90-0
DPG Methyl Ether	3459-09-48
Tributoxyethyl Phosphate	78-51-3
Zinc Ammonium Carbonate	38714-47-5
Isodecyl Benzoate	131298-44-7

NFPA

HAZARD RATING:

4-EXTREME
3-HIGH
2-MODERATE
1-SLIGHT

To Reorder:

WECHEM, INC.

5734 Susitna Dr. * Harahan, LA 70123

(504) 733-1152 * 1-800-426-0512

FAX: (504) 733-2218 * WEICHEM.COM

MADE IN THE USA

READ MATERIAL SAFETY DATA SHEET BEFORE USE

NET CONTENTS: 2.5 U.S. GALLONS BATCH #