

PENETRATING HIGH TACK FORMULA

A high tack, clear, lubricating gel which provides lubrication at temperatures from -30°F to +500°F. Penetrates as an oil to lubrication point, then forms into a tacky grease-like gel. Deposits a fine polytetrafluoroethylene and gel lubricant mixture deep inside working parts. Resists water washout and weathering. Prevents rust and corrosion while covering surfaces with a moisture proof barrier film. Safe on most plastics.

USE ON:

Gears, sprockets, hinges, chains, cable, wire rope, slides, valves, pistons, rings, seals, bearings, sleeves, cams and bushings.

USED BY:

Machine shops, light and heavy manufacturing, HVAC, plumbing and other trades. Automotive and virtually all maintenance or repair operations.

DIRECTIONS:

SHAKE WELL BEFORE USING

Remove cap and rotate actuator until orifice is pointed toward mark on valve cup. Spray holding can 12 to 14 inches away from surface to be treated. For hard to reach areas, insert extension tube into actuator orifice.



Engineered Chemistries
SUPERIOR SOLUTIONS

Ultra Gel Lube™

Penetrating Gel Lubricant With PTFE

- High Tack
- Safe on Most Plastic
- Effective From -30°F to +500°F

NET WT. 12 OZ. (340 Grams)

**DANGER: EXTREMELY FLAMMABLE
HARMFUL OR FATAL IF SWALLOWED
CONTENTS UNDER PRESSURE
SEE OTHER CAUTIONS ON SIDE PANEL**

DANGER: May irritate eyes, skin, and respiratory passages. Use only in a well ventilated area. Avoid contact with eyes or prolonged contact with skin. Do not use near heat, sparks or open flame. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

KEEP OUT OF REACH OF CHILDREN

CONTAINS:

CAS#

Heptane, Branched, Cyclic, Linear.....	426260-76-6
Acetone.....	67-64-1
White Mineral Oil.....	8042-47-5
Carbon Dioxide.....	124-38-9

NFPA

HAZARD RATING:



PROPER SHIPPING NAME:

Consumer Commodity, ORM-D

READ MATERIAL SAFETY DATA SHEET BEFORE USE

To Reorder: **WECHEM, INC.**

5734 Susitna Drive • Harahan, LA 70123

LOCAL: (504) 733-1152 • FAX: (504) 733-2218

1-800-426-0512 • www.wechem.com



REV 04/11