

1010955 / 95814 RM_MFD 03/31/11

- METALLIC COATINGS (MCP) DO NOT EXCEED 80% VOC OR 1.90 MIR.
- EQUIVALENT TO HOT DIP ZINC GALVANIZING
- HIGHLY RESISTANT TO SALT CORROSION AND WATER
- ELECTRO-MECHANICAL PROCESS CAUSE HEALING ACTION WHERE SURFACE IS SCRATCHED OR BROKEN

DESCRIPTION:

ZINKOTE is an advanced resin compound containing high concentrations of zinc particles used as an anti-corrosion and protective coating on metal surfaces. It is not a zinc colored paint. **ZINKOTE** kills rust on contact and forms a durable shield to prevent surface destruction. **ZINKOTE** can be painted over after sufficient cure time.

TYPICAL USES:

Oil Rigs, Signs and Fencing, Tanks and Piping, Structural Steel and Wire, Fans, Ducts and Culverts, Dairy Equipment, Air Conditioning Units, Road and Farm Equipment and anywhere that metal is subject to rust and corrosion.

DIRECTIONS:

Shake! Shake! Shake can vigorously until agitator begins to rattle and continue for one full minute, to put all zinc into suspension. Shake frequently during use. Surface must be free from all loose rust, oil, grease, oil paint, etc. Spray no closer than 10 to 12 inches from surface with a sweeping motion. Should be touch dry in 15 minutes; may be painted approximately 6 hours after drying. Several thin coats are better than one heavy coat.

IMPORTANT - To prevent clogging, invert can and spray a few short bursts after each use.



- ELECTRO-CHEMICAL BOND
- RUST PROOFS METAL
- STOPS CORROSION
- LONG-LASTING

DANGER: Use only in a well ventilated area. Sensitive to static discharge. Do not use near heat, sparks or open flame. Avoid contact with eyes or prolonged contact with skin. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.

FIRST AID: IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

CONTAINS:		CAS#
Liquefied Petroleum Gas.....	68476-86-8	
Toluene.....	108-88-3	
Zinc.....	7440-66-6	
Petroleum Distillates.....	64742-47-8	

NFPA	HAZARD RATING:
<p>Health: 4 Flammability: 2 Specific Hazard: 1 Reactivity: 0</p>	<p>4-EXTREME 3-HIGH 2-MODERATE 1-SLIGHT 0-INSIGNIFICANT</p>

PROPER SHIPPING NAME:
Consumer Commodity, ORM-D

READ MATERIAL SAFETY DATA SHEET BEFORE USE
KEEP AWAY FROM CHILDREN



**Engineered Chemistries
SUPERIOR SOLUTIONS**

WECHEM, INC.
5734 Susitna Dr. Harahan, LA 70123
504.733.1152 · 1.800.426.0512
FAX 504.733.2218 · www.wechem.com

03/11

NET WT. 14 OZ. (396 Grams)