

C-130 cools threads and pipe during operation thereby improving thread quality!

C-130's clear, light color allows operators to better see the machined part during the cutting operation. It has a low odor and contains an ISOSYN base stock, which provides better thermal and oxidation stability for longer fluid life. The ISOSYN base stock also increases oil life and creates a safer work environment by increasing the fluid's flash point and lowering exposure to aromatics and product vapor, smoking and misting. The chlorine-free nature of the fluid reduces the cost of disposal at the end of the fluid life.



C-130™

**CUTTING AND
THREADING OIL**



- **READY TO USE FORMULA**
- **ANTI-CORROSIVE**
- **COOLS AND LUBRICATES**

CAUTION
KEEP OUT OF REACH OF CHILDREN

FOR INDUSTRIAL USE ONLY
SEE RIGHT PANEL FOR ADDITIONAL PRECAUTIONS AND FIRST AID STATEMENTS.

Net Contents: U.S. Quart (32 FL. OZ.)

CAUTION:
Avoid contact with eyes and prolonged contact with skin.

FIRST AID

EYES: Flush with water for 15 minutes. Seek medical attention.

SKIN: Wash with soap and water. If irritated, seek medical attention

INHALATION: Remove to fresh air. Resuscitate if necessary. Get medical attention.

INGESTION: Do not induce vomiting. Drink two large glasses of water. Get immediate medical attention.

CONTAINS: Highly Refined Mineral Oil (C15-C50).....**CAS #** N/A



HAZARD RATING:
4-EXTREME
3-HIGH
2-MODERATE
1-SLIGHT

Proper Shipping Name:
Petroleum Oils, Greases

READ MATERIAL SAFETY DATA SHEET BEFORE USE.

WECHEM, INC.
5734 Susitna Dr
Harahan, LA 70123
(504) 733-1152
800-426-0512
FAX (504) 733-2218
WWW.WECHEM.COM

