

A clear, synthetic coolant and lubricating fluid for machining, punching, sawing, milling, boring, cutting, grinding, tapping and threading operations on all steels and non-ferrous metals.

Results in cooler work piece, less heat distortion and less tool burning which increases production rates and tool life.

Transparency of fluid allows for excellent visibility of work area.


Use extensively for portable operations, field operations and any cutting, drilling or tapping machinery equipped with its own recycling system. Fluid can be removed with cold water or degreasing solvents.

COOLS THESE SURFACES:

Aluminum and Aluminum Alloys, Carbon Steels, Stainless Steels, Chrome-Moly and Vanadium Steels, Nitralloy Steel, Iconel, Monel, Phosphor, Bronze, Titanium, Hastelloy Alloys, Berylium, Copper and other related alloys.

DIRECTIONS:

Product can be sprayed on, brushed on or used in automatic recirculating systems. Apply a liberal amount directly to work area, Reapply as necessary to keep area cool and well lubricated.



**COOLANT LUBRICANT FOR
DRILLS • TAPS • CUTTING TOOLS**

NET CONTENTS: 5 GALLONS REV 07-07

DANGER: FLAMMABLE
KEEP OUT OF REACH OF CHILDREN
HARMFUL OR FATAL IF SWALLOWED
SEE OTHER CAUTIONS ON SIDE PANEL

DANGER: Do not use near heat or open flame. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 120°F.


FIRST AID:

IF EYE CONTACT: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately. **IF SKIN CONTACT:** Wash with soap and water. If irritation persists seek medical attention. **EXCESSIVE INHALATION:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **IF INGESTED:** Do not induce vomiting. Seek medical attention immediately.

KEEP OUT OF REACH OF CHILDREN

For further information consult
Material Safety Data Sheet.

CONTAINS:	CAS#
Ethyl Alcohol	64-17-5
Polyalkylene Glycol Monobutyl Ether.....	9038-95-3
Amine containing Alcohol.....	Trade Secret

NFPA	HAZARD RATING:
	4-EXTREME 3-HIGH 2-MODERATE 1-SLIGHT 0-INSIGNIFICANT

PROPER SHIPPING NAME:
Flammable Liquids, N.O.S. (Ethyl Alcohol), 3, UN 1993, PGIII

READ MATERIAL SAFETY DATA SHEET BEFORE USE

To Reorder:

WEICHEM, INC.

5734 Susitna Drive, Harahan, LA 70123

LOCAL: (504) 733-1152

FAX: (504) 733-2218

1-800-426-0512

www.wechem.com