

Brite

MSDS Number: A35E

Revision Date: 05/21/09

Page 1 of 4

1	PRODUCT AND COMPANY IDENTIFICATION
----------	---

Manufacturer

Distributed By: Wechem, Inc
5734 Susitna Dr
Harahan, LA 70123

Contact: Charito Kuylen
Phone: 504-733-1152
Fax: 504-733-2218
Web: www.wechem.com

Product Name: Brite
Revision Date: 05/21/09
MSDS Number: A35E
Product Code: A35

2	HAZARDS IDENTIFICATION
----------	-------------------------------

Route of Entry: Inhalation, ingestion, eye

Inhalation: Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to the upper respiratory tract, anesthesia, dizziness, headache, rapid breathing, narcosis and other central nervous system effects, including unconsciousness and death.

Skin: Frequent or prolonged contact may cause irritation and possibly dermatitis. May aggravate existing skin conditions.

Eye: May cause moderate to severe irritation, accompanied by stinging, tearing, redness, blurred vision and pain.

Ingestion: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into lungs can cause severe pulmonary injury, possibly progressing to death.

3	COMPOSITION/INFORMATION ON INGREDIENTS
----------	---

Ingredients:

Cas #	Chemical Name	Perc.	OSHA PEL (ppm)	ACGIH TLV(ppm)	Carcin Ref.
64741668	Isoparaffinic Hydrocarbon	1-10	N/A	281**	D
8042475	white Mineral Oil	35-45	5mg/m3*	5mg/m3*	D
68476868	Liquefied Petroleum Gas	20-30	1000	1000	D
67641	Acetone	5-15	1000	500	D

*Exposure limits for mist

**Manufacturer's Recommended Exposure Limit (REL) TWA

Brite

MSDS Number: A35E

Revision Date: 05/21/09

Page 2 of 4

4 FIRST AID MEASURES

Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.
Skin Contact: Wash with soap and water. If irritated, seek medical attention.
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.
Ingestion: Do not induce vomiting. Get immediate medical attention.

5 FIRE FIGHTING MEASURES

Flammability: Extremely Flammable Spray
Flash Point: (Conc. only) : < 2 Deg. F.
Flash Point Method: TCC
Burning Rate: ND
Autoignition Temp: ND
LEL: ND
UEL: ND

Extinguishing media: Foam, dry media, carbon dioxide

Special Fire fighting procedures: Wear self-contained breathing apparatus and protective clothing. Cool fire-exposed containers to prevent rupturing.

Unusual Fire & Explosion Hazards: Exposure to temperature above 120 Deg. F. may cause bursting.

6 ACCIDENTAL RELEASE MEASURES

Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. Absorb with suitable medium. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping.

7 HANDLING AND STORAGE

Handling Precautions: Store in a cool, dry area away from heat, sparks, flame, or any other sources of ignition
 NFPA code 30B Rating: Level 3 aerosol
Storage Requirements: Store in a cool, dry area away from heat, sparks, flame, or any other sources of ignition. Keep out of reach of children. For industrial and institutional use only. Do not store at temperatures above 120 Deg. F.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Ventilation Requirement: Local exhaust to keep TLV below acceptable limits
Personal Protective Equip: HMIS PP, B | Goggles, Gloves
 Respiratory Protection: None needed for proper use in accordance with label directions
 Protective gloves: Chemical Resistant gloves if hand contact will be made
 Eye protection: Safety glasses/ chemical proof goggles

Hygienic work practices: Wash with soap and water before handling food.

Brite

MSDS Number: A35E

Revision Date: 05/21/09

Page 3 of 4

9	PHYSICAL AND CHEMICAL PROPERTIES
----------	---

Appearance:	Clear, colorless liquid		
Physical State:	Liquid	Odor:	Mint
Particle Size:	NA	Molecular Formula:	NA
Spec Grav./Density:	(H2O=1):Conc: 0.825 @ 75 Deg.F.	Solubility:	Negligible
Viscosity:	NA	Softening Point:	NA
Sat. Vap. Concentrat.:	NA	Percent Volatile:	NA
Boiling Point:	120 Deg. F.	Heat Value:	NA
Vapor Pressure:	50 PSIG @ 72 Deg. F.(can)	Freezing/Melting Pt.:	NA
pH:	NA	Octanol:	NA
Evap. Rate:	NA	Vapor Density:	(Air=1) > 1
Molecular weight:	NA	VOC:	~ 30%
		Bulk Density:	NA

10	STABILITY AND REACTIVITY
-----------	---------------------------------

Stability:	Stable		
Conditions to Avoid:	Contact with strong oxidizing agents, heat		
Materials to Avoid:	Strong oxidizing agents, chloroform, alkalis, chlorine compounds, acids and potassium 1-butoxide		
Hazardous Decomposition:	Carbon dioxide, carbon monoxide		
Hazardous Polymerization:	Will not occur		

11	TOXICOLOGICAL INFORMATION
-----------	----------------------------------

NA

12	ECOLOGICAL INFORMATION
-----------	-------------------------------

NA

13	DISPOSAL CONSIDERATIONS
-----------	--------------------------------

Dispose of according to local, state, or federal regulations.

14	TRANSPORT INFORMATION
-----------	------------------------------

Proper Shipping Name: Consumer Commodity, ORM-D

Brite

MSDS Number: A35E

Revision Date: 05/21/09

Page 4 of 4

15

REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

*Acetone (67641 5-15%) CERCLA, HAP, MASS, NJHS, OSHAWAC, PA, TOXICRCRA, TXAIR, TXHWL

REGULATORY KEY DESCRIPTIONS

MASS = MA Massachusetts Hazardous Substances List
OSHAWAC = OSHA workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
TXAIR = TX Air Contaminants with Health Effects Screening Level
CERCLA = Superfund clean up substance
HAP = Hazardous Air Pollutants
NJHS = NJ Right-to-Know Hazardous Substances
SARA313 = SARA 313 Title III Toxic Chemicals
TOXICRCRA = RCRA Toxic Hazardous Wastes (U-List)
TXHWL = TX Hazardous Waste List

16

OTHER INFORMATION

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. ** Chemical listed as carcinogen or potential carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not listed [e] Animal Data only
N/A = Not available N/D = Not determined