



Clear View

MSDS Number: A55D

Revision Date: 05/26/09

Page 1 of 4

1 PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Wechem, Inc
5734 Susitna Dr

Harahan, LA 70123

Contact: Charito Kuylen
Telephone Number: 504-733-1152
FAX Number: 504-733-2218
E-Mail:
Web www.wechem.com

Product Name: Clear View
Revision Date: 05/26/09
MSDS Number: A55D
Product Code: A55

2 HAZARDS IDENTIFICATION

Route of Entry: Inhalation, ingestion, eye, skin absorption
Target Organs: NA
Inhalation: Inhalation of small amounts of vapor or mist is not likely to cause harmful effects. Inhalation of large amounts may irritate the upper respiratory tract and have a slight anesthetic effect. Prolonged overexposure can cause central nervous system depression, mild temporary changes in the liver, effects on heart and breathing rate, low blood pressure.
Skin Contact: May cause mild irritation. Frequent or prolonged contact may cause redness, burning, drying and cracking of skin. May aggravate existing skin conditions.
Eye Contact: May cause irritation accompanied by stinging, tearing, redness and swelling of eyes.
Ingestion: Ingestion of small amounts during normal handling and use is not likely to cause harmful effects. Ingestion of large amounts can cause severe gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into lungs can cause lung inflammation and other lung injuries.

HMIS II-ratings (scale 0-4): Health = 1, Fire = 1, Reactivity = 0
HMIS III-ratings (scale 0-4): Health = 1, Fire = 1, Physical Hazard = 0
NFPA-ratings (scale 0-4): Health = 1, Fire = 1, Reactivity = 0

3 COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas #	Perc.	Chemical Name	OSHA PEL (ppm)	ACGIH TLV (PPM)	Carcin. Ref.
67630	1-10	Isopropyl alcohol	400	400	D
68476868	1-10	Liquefied Petroleum Gas	1000	1000	D



4 FIRST AID MEASURES

Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.
Skin Contact: Wash with soap and water. If irritated, seek medical attention.
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.
Ingestion: Do not induce vomiting. Get immediate medical attention.

5 FIRE FIGHTING MEASURES

Flash Point: None to boiling (212 Deg.F)
Flash Point Method: TOC
Burning Rate: ND
Autoignition Temperature: ND
LEL: ND
UEL: ND
Flammability Classification: (Per CSMA Flame Projection Test) : Non-flammable spray

Extinguishing media: Foam, dry chemical, carbon dioxide

Special Fire fighting procedures: Wear self-contained breathing apparatus and protective clothing. Cool fire-exposed containers to prevent rupturing.

Unusual Fire & Explosion Hazard: Expose to temperature above 120 Deg. F. may cause bursting.

6 ACCIDENTAL RELEASE MEASURES

Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks heat sources and open flame far away from spill or leak. Absorb with suitable medium. Wash area to prevent slipping.

7 HANDLING AND STORAGE

Handling Precautions: Store in a cool, dry area away from heat, sparks, flame, or any other sources of ignition. For industrial and institutional use only.
Storage Requirements: Store in a cool, dry area away from heat, sparks, flame, or any other sources of ignition. Keep out of reach of children.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Ventilation Requirement: Local exhaust to keep TLV below acceptable limits.
Protective Equipment: HMIS PP, B | Goggles, Gloves
HMIS PP, A | Goggles
Respiratory Protection: None needed for proper use in accordance with label directions.
Protective gloves: Chemical resistant
Eye protection: Safety glasses/ goggles
Exposure Guidelines/Other: Hygienic work practices: Wash with soap and water before handling food.



Clear View

MSDS Number: A55D

Revision Date: 05/26/09

Page 3 of 4

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear, colorless liquid	Boiling Point:	212 Deg. F.
Physical State:	(Conc.): Liquid	Freezing/Melting Pt.:	NA
Odor:	Light alcohol	Solubility:	Complete
pH:	9.8	Spec Grav./Density:	(H2O=1): 0.99 @ 70 Deg. F.
Vapor Pressure:	(Can, psig at 72 Deg F): 50		
Vapor Density:	(Air=1) > 1		
Heat Value:	NA		
VOC:	9.53		
Evap. Rate:	NA		
Bulk Density:	NA		
Octanol:	NA		
Molecular Weight:	NA		
Particle Size:	NA		
Softening Point:	NA		
Viscosity:	NA		
Percent Volatile:	NA		
Sat. Vap. Concentrat.:	NA		
Molecular Formula:	NA		

10 STABILITY AND REACTIVITY

Stability:	Stable
Conditions to avoid:	Contact with strong oxidizing agents, heat
Materials to avoid (incompatibility):	Strong oxidizing agents
Hazardous Decomposition products:	Carbon dioxide, carbon monoxide
Hazardous Polymerization:	Will not occur

11 TOXICOLOGICAL INFORMATION

NA

12 ECOLOGICAL INFORMATION

NA

13 DISPOSAL CONSIDERATIONS

Dispose of according to local, state, or federal regulations.



Clear View

MSDS Number: A55D

Revision Date: 05/26/09

Page 4 of 4

14 TRANSPORT INFORMATION

Proper Shipping Name: Consumer Commodity, ORM-D

15 REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

*Isopropyl alcohol (67630 1-10%) MASS, NJHS, NRC, OSHAWAC, PA, TXAIR

*Liquefied Petroleum Gas (68476868 1-10%) MASS, OSHAWAC, PA, TXAIR

REGULATORY KEY DESCRIPTIONS

MASS = MA Massachusetts Hazardous Substances List
NJHS = NJ Right-to-Know Hazardous Substances
NRC = Nationally Recognized Carcinogens
OSHAWAC = OSHA Workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
TXAIR = TX Air Contaminants with Health Effects Screening Level

16 OTHER INFORMATION

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. ** Chemical listed as carcinogen or potential carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not listed [e] Animal Data only
N/A = Not available N/D = Not determined

END OF MSDS DOCUMENT