

MSDS Material Safety Data Sheet

Wechem, Inc.



Cutter

MSDS Number: A290E

Revision Date: 06/01/09

Page 1 of 4

1 PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Wechem, Inc
5734 Susitna Dr

Harahan, LA 70123

Contact: Charito Kuylen
Telephone Number: 504-733-1152
FAX Number: 504-733-2218
E-Mail:
Web www.wechem.com

Product Name: Cutter
Revision Date: 06/01/09
MSDS Number: A290E
Product Code: A290

2 HAZARDS IDENTIFICATION

Route of Entry: Inhalation, ingestion, eye
Target Organs: NA
Inhalation: Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to the upper respiratory tract, dizziness, nausea and other central nervous system effects.
Skin Contact: Frequent or prolonged contact may cause irritation.
Eye Contact: May cause moderate to severe irritation, stinging, redness, tearing and blurred vision. Prolonged exposure may injure eye tissue.
Ingestion: Can cause gastrointestinal irritation, nausea, vomiting, diarrhea. Aspiration of material into lungs can cause pulmonary injury.

HMIS II-ratings (scale 0-4): Health = 1, Fire = 2, Reactivity = 0

HMIS® Rating H*1/F2/PH0

NFPA-ratings (scale 0-4): Health = 1, Fire = 2, Reactivity = 0

3 COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas #	Chemical Name	Perc.	OSHA PEL (ppm)	ACGIH TLV(ppm)	Carcin. Ref.
68476868	Liquefied Petroleum Gas	10-30	1000	1000	D
111900	Diethylene Glycol Monoethyl Ether	1-10	NA	25	D
111422	Diethanolamine	1-10	3	0.46	D
5989275	Citrus Terpene	20-30	NA	NA	D



Cutter

MSDS Number: A290E

Revision Date: 06/01/09

Page 2 of 4

4 FIRST AID MEASURES

Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.
Skin Contact: Wash with soap and water. If irritated, seek medical attention.
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.
Ingestion: Do not induce vomiting. Get immediate medical attention.

5 FIRE FIGHTING MEASURES

Flash Point: 125 Deg. F.
Flash Point Method: PMCC
Burning Rate: ND
Autoignition Temperature: ND
LEL: ND
UEL: ND
Flammability Classification: Per CSMA Flame Projection Test : Non-flammable spray

Extinguishing media: Foam, dry chemical, carbon dioxide

Special Fire fighting procedures: Wear self-contained breathing apparatus and protective clothing.

Unusual Fire & Explosion Hazard: Exposure to temperature above 120 Deg. F. may cause bursting.

6 ACCIDENTAL RELEASE MEASURES

Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping.

7 HANDLING AND STORAGE

Handling Precautions: Store in a cool, dry area away from heat, sparks, flame, or any other sources of ignition. For industrial and institutional use only.

Storage Requirements: Store in a cool, dry area away from heat, sparks, flame, or any other sources of ignition. Keep out of reach of children.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Ventilation Requirement: Local exhaust to keep TLV below acceptable limits.
Protective Equipment: HMIS PP, B | Goggles, Gloves

Respiratory Protection: None needed for proper use in accordance with label directions.

Protective gloves: Chemical resistant gloves if hand contact will be made.

Eye protection: Safety glasses/ goggles

Exposure Guidelines/Other: Hygienic work practices: Wash with soap and water before handling food.



Cutter

MSDS Number: A290E

Revision Date: 06/01/09

Page 3 of 4

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	White foam	Boiling Point:	212 Deg. F.
Physical State:	(Conc): Liquid	Freezing/Melting Pt.:	NA
Odor:	Citrus	Solubility:	Complete
pH:	10.3 +/- 1	Spec Grav./Density:	(H2O=1): 0.98 @ 75 Deg. F.
Vapor Pressure:	(Can PSIG @ 72 Deg. F): 55		
Vapor Density:	(Air=1) > 1		
Heat Value:	NA		
VOC:	40.2 %		
Evap. Rate:	NA		
Bulk Density:	NA		
Octanol:	NA		
Molecular Weight:	NA		
Particle Size:	NA		
Softening Point:	NA		
Viscosity:	NA		
Percent Volatile:	NA		
Sat. Vap. Concentrat.:	NA		
Molecular Formula:	NA		

10 STABILITY AND REACTIVITY

Stability:	Stable
Conditions to avoid:	Contact with incompatible materials, heat
Materials to avoid (incompatibility):	Strong oxidizing agents
Hazardous Decomposition products:	Carbon dioxide, carbon monoxide
Hazardous Polymerization:	Will not occur

11 TOXICOLOGICAL INFORMATION

NA

12 ECOLOGICAL INFORMATION

NA

13 DISPOSAL CONSIDERATIONS

Dispose of according to local, state, or federal regulations.



Cutter

MSDS Number: A290E

Revision Date: 06/01/09

Page 4 of 4

14 TRANSPORT INFORMATION

Proper Shipping Name: Consumer Commodity, ORM-D

15 REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

*Liquefied Petroleum Gas (68476868 10-30%) MASS, OSHAWAC, PA, TXAIR

*Diethylene Glycol Ethyl Ether (111900 1-10%) HAP, MASS, PA,
SARA 313

*Diethanolamine (111422 1-10%) CERCLA, HAP, MASS, NJHS, OSHAWAC, PA, SARA313, TXAIR

REGULATORY KEY DESCRIPTIONS

MASS = MA Massachusetts Hazardous Substances List
OSHAWAC = OSHA Workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
TXAIR = TX Air Contaminants with Health Effects Screening Level
HAP = Hazardous Air Pollutants
CERCLA = Superfund clean up substance
NJHS = NJ Right-to-Know Hazardous Substances
SARA313 = SARA 313 Title III Toxic Chemicals

16 OTHER INFORMATION

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. ** Chemical listed as carcinogen or potential carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not listed [e] Animal Data only
N/A = Not available N/D = Not determined

END OF MSDS DOCUMENT