



Protecto Flex

MSDS Number: L754D

Revision Date: 05/25/06

Page 1 of 4

1 PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Wechem, Inc
5734 Susitna Dr

Harahan, LA 70123

Contact: Charito Kuylen
Telephone Number: 504-733-1152
FAX Number: 504-733-2218
E-Mail:
Web www.wechem.com

Product Name: Protecto Flex
Revision Date: 05/25/06
MSDS Number: L754D
Product Code: L754

2 HAZARDS IDENTIFICATION

Route of Entry: Inhalation, ingestion, skin absorption, eye
Target Organs: NA
Inhalation: Excessive inhalation may cause nasal and respiratory irritation, central nervous system effects.
Skin Contact: Prolonged contact can cause moderate irritation, defatting, dermatitis
Eye Contact: Can cause severe irritation, redness, tearing, blurred vision.
Ingestion: Can cause gastrointestinal irritation, nausea, diarrhea, vomiting.

HMIS II-ratings (scale 0-4): Health = 1, Fire = 2, Reactivity = 0
HMIS III-ratings (scale 0-4): Health = 1, Fire = 2, Physical Hazard = 1
NFPA-ratings (scale 0-4): Health = 1, Fire = 2, Reactivity = 0

3 COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas #	Chemical Name	Perc.	OSHA PEL (ppm)	ACGIH TLV(ppm)	Carcin. Ref.
64742887	Aliphatic Petroleum Distillates	1-10	100	100	D
8052413	Aliphatic Hydrocarbon	15-25	100	100	D
68425343	Calcium Salt of Oxidized Petrolatum	> 60	NA	NA	D



Protecto Flex

MSDS Number: L754D

Revision Date: 05/25/06

Page 2 of 4

4 FIRST AID MEASURES

Inhalation: Remove to fresh air. Resuscitate if necessary. Seek medical attention.
Skin Contact: Wash with soap and water. If irritated seek medical attention.
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.
Ingestion: Do not induce vomiting. Get medical attention.

5 FIRE FIGHTING MEASURES

Flash Point: 107 Deg. F.
Flash Point Method: NA
Burning Rate: ND
Autoignition Temperature: ND
LEL: ND
UEL: ND
Flammability Classification: Combustible

Extinguishing media: Foam, dry chemical, carbon dioxide

Special Fire fighting procedures: Use self-contained breathing apparatus and protective clothing.

Unusual Fire & Explosion Hazard: Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flames and ignition sources at locations distant from materials handling point.

6 ACCIDENTAL RELEASE MEASURES

Absorb with suitable medium.

7 HANDLING AND STORAGE

Handling Precautions: Store in a cool, dry area away from heat, flame and other sources of ignition because product (even just residue) can ignite explosively.
Storage Requirements: Store in a cool, dry area away from heat, flame and other sources of ignition because product (even just residue) can ignite explosively. Keep out of reach of children.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Ventilation Requirement: Mechanical (General or local) ventilation to keep TLV below exposure limits.
Protective Equipment: HMIS PP, B | Goggles, Gloves
Respiratory Protection: NIOSH/ MSHA approved respirator advised in absence of proper ventilation.
Protective gloves: Neoprene/ Chemical resistant
Eye protection: Safety glasses/ goggles
Exposure Guidelines/Other: Hygienic work practices: Wash with soap and water before handling food. Remove contaminated clothing.



Protecto Flex

MSDS Number: L754D

Revision Date: 05/25/06

Page 3 of 4

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Brownish liquid	Boiling Point:	NA
Physical State:	Liquid	Freezing/Melting Pt.:	NA
Odor:	Solvent	Solubility:	Negligible
pH:	NA	Spec Grav./Density:	(H2O=1): Conc. only= 0.866 +/- 0.05
Vapor Pressure:	NA		
Vapor Density:	(Air=1): >1		
Heat Value:	NA		
VOC:	NA		
Evap. Rate:	NA		
Bulk Density:	NA		
Octanol:	NA		
Molecular Weight:	NA		
Particle Size:	NA		
Softening Point:	NA		
Viscosity:	NA		
Percent Volatile:	NA		
Sat. Vap. Concentrat.:	NA		
Molecular Formula:	NA		

10 STABILITY AND REACTIVITY

Stability:	Stable
Conditions to avoid:	Contact with strong oxidizing agents
Materials to avoid (incompatibility):	Strong oxidizing agents
Hazardous Decomposition products:	May form: Carbon monoxide, Carbon dioxide, various hydrocarbons
Hazardous Polymerization:	Will not occur

11 TOXICOLOGICAL INFORMATION

NA

12 ECOLOGICAL INFORMATION

NA

13 DISPOSAL CONSIDERATIONS

Dispose of according to local, state, or federal regulations.



Protecto Flex

MSDS Number: L754D

Revision Date: 05/25/06

Page 4 of 4

14 TRANSPORT INFORMATION

Proper Shipping Name: Not Regulated

15 REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

*Aliphatic Petroleum Distillate (8052413 15-25%) MASS, OSHAWAC, PA, TXAIR

REGULATORY KEY DESCRIPTIONS

MASS = MA Massachusetts Hazardous Substances List
OSHA = OSHA workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
TXAIR = TX Air Contaminants with Health Effects Screening Level

16 OTHER INFORMATION

We believe the statements technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. ** Chemical listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not listed [e] Animal data only
N/A = Not available N/D = Not determined

END OF MSDS DOCUMENT