

MSDS *Material Safety Data Sheet*

Wechem, Inc.



White Lightning

MSDS Number: A250E

Revision Date: 02/01/10

Page 1 of 5

1 PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Distributed By: Wechem, Inc
5734 Susitna Dr

Harahan, LA 70123

Contact: Charito Kuylen
Telephone Number: 504-733-1152
FAX Number: 504-733-2218
E-Mail:
Web www.wechem.com

Product Name: White Lightning
Revision Date: 02/01/10
MSDS Number: A250E
Product Code: A250

2 HAZARDS IDENTIFICATION

Route of Entry: Inhalation, eye
Target Organs: NA
Inhalation: Inhalation of mist can cause irritation of nasal passages. Abusive or excessive inhalation may cause irritation to the upper respiratory tract, dizziness, nausea and other central nervous system effects, including paralysis, loss of consciousness and even death.
Skin Contact: Frequent or prolonged contact may cause irritation.
Eye Contact: May cause irritation, pain, redness or burning.
Ingestion: May be harmful or fatal if swallowed. Can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. Aspiration of material into the lungs can cause lung inflammation and damage.

HMIS II-ratings (scale 0-4): Health = 1, Fire = 3, Reactivity = 0
HMIS III-ratings (scale 0-4): Health = 1, Fire = 3, Physical Hazard = 0
NFPA-ratings (scale 0-4): Health = 1, Fire = 4, Reactivity = 0



White Lightning

MSDS Number: A250E

Revision Date: 02/01/10

Page 2 of 5

3 COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

Cas #	Chemical Name	Perc.	OSHA PEL (ppm)	ACGIH TLV(ppm)	Carcin. Ref.
64742489	Naphtha (Petroleum), Hydrotreated Heavy	5-15	100	100	D
67641	Acetone	30-40	750	750	D
64742898	Naphtha (Petroleum), Light Aliphatic	1-10	100	100	D
64742490	Naphtha (petroleum), Hydrotreated Light	1-10	NA	346*	D
1314132	Zinc Oxide**	0-5	NA	2mg/m ³	D
68476868	Liquefied Petroleum Gas	20-30	1000	1000	D

* Manufacturer's recommended exposure limit (TWA-8 hr)

**Product contains less than 3% Zinc (7440-66-6) in the form of zinc oxide.

4 FIRST AID MEASURES

Inhalation:	Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.
Skin Contact:	Wash with soap and water. If irritated seek medical attention.
Eye Contact:	Flush with water for 15 minutes. If irritated, seek medical attention.
Ingestion:	Do not induce vomiting. Get medical attention.

5 FIRE FIGHTING MEASURES

Flash Point:	<5 Deg. F.
Flash Point Method:	TOC
Burning Rate:	ND
Autoignition Temperature:	ND
LEL:	ND
UEL:	ND
Flammability Classification:	(PER CSMA Flame Projection Test): Extremely Flammable Spray

Extinguishing media: Foam, dry chemical, carbon dioxide

Special Fire fighting procedures: Use self-contained breathing apparatus and protective clothing. Cool fire-exposed containers to prevent rupturing.

Unusual Fire & Explosion Hazard: Exposure to temperature above 120 Deg. F. may cause bursting.

6 ACCIDENTAL RELEASE MEASURES

Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws.



White Lightning

MSDS Number: A250E

Revision Date: 02/01/10

Page 3 of 5

7 HANDLING AND STORAGE

Handling Precautions: Store in a cool, dry area away from sparks, flame and other sources of ignition. For Industrial and Institutional use only.

Storage Requirements: Store in a cool, dry area away from sparks, flame and other sources of ignition. Keep out of reach of children.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Ventilation Requirement: Local exhaust to keep TLV below acceptable limits.

Protective Equipment: HMIS PP, B | Goggles, Gloves
Respiratory Protection: None needed in accordance with label directions.
Protective gloves: Use chemical resistant gloves to prevent skin contact.
Eye protection: Safety glasses / Chemical proof goggles

Exposure Guidelines/Other: Hygienic work practices: Wash with soap and water before handling food.

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Off-white, opaque liquid	Boiling Point:	135 Deg. F.
Physical State:	Liquid	Freezing/Melting Pt.:	NA
Odor:	Solvent	Solubility:	Slight
pH:	NA	Spec Grav./Density:	(H2O=1): 0.7955 @ 70 Deg. F.
Vapor Pressure:	(Can; psig @72 Deg. F): 55		
Vapor Density:	(Air=1): > 1		
Heat Value:	NA		
VOC:	49.00 %		
Evap. Rate:	NA		
Bulk Density:	NA		
Octanol:	NA		
Molecular Weight:	NA		
Particle Size:	NA		
Softening Point:	NA		
Viscosity:	NA		
Percent Volatile:	NA		
Sat. Vap. Concentrat.:	NA		
Molecular Formula:	NA		

10 STABILITY AND REACTIVITY

Stability: Material stable

Conditions to avoid: Contact with acids, alkalis, reducing agents, strong oxidizing agents, heat

Materials to avoid (incompatibility): Avoid contact with acids, alkalis, reducing agents, strong oxidizing agents

Hazardous Decomposition products: Carbon Monoxide, Carbon Dioxide, Zinc Oxides. Sulfur Oxides and asphyxiants

Hazardous Polymerization: Will not occur

MSDS *Material Safety Data Sheet* Wechem, Inc.



White Lightning

MSDS Number: A250E

Revision Date: 02/01/10

Page 4 of 5

11 TOXICOLOGICAL INFORMATION

NA

12 ECOLOGICAL INFORMATION

NA

13 DISPOSAL CONSIDERATIONS

Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State, and local authorities for approval procedures.

14 TRANSPORT INFORMATION

Proper Shipping Name: Consumer Commodity, ORM-D



White Lightning

MSDS Number: A250E

Revision Date: 02/01/10

Page 5 of 5

15 REGULATORY INFORMATION

COMPONENT / (CAS/PERC) / CODES

- *Zinc oxide (1314132 0-5%) MASS, OSHAWAC, PA, TXAIR
- *Naphtha, petroleum, hydrotreated heavy (64742489 1-10%) TSCA
- *Acetone (67641 30-40%) CERCLA, HAP, MASS, NJHS, OSHAWAC, PA, TOXICRCRA, TSCA, TXAIR, TXHWL
- *Solvent naphtha, petroleum, light aliph. (64742898 1-10%) TSCA
- *Petroleum gases, liquefied, sweetened (68476868 20-30%) TSCA
- *Propane/ Isobutane (68476868 1-10%) TSCA

REGULATORY KEY DESCRIPTIONS

MASS = MA Massachusetts Hazardous Substances List
OSHAWAC = OSHA Workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
TXAIR = TX Air Contaminants with Health Effects Screening Level

TSCA = Toxic Substances Control Act

CERCLA = Superfund clean up substance
HAP = Hazardous Air Pollutants
NJHS = NJ Right-to-Know Hazardous Substances
TOXICRCRA = RCRA Toxic Hazardous Wastes (U-List)
TXHWL = TX Hazardous Waste List

16 OTHER INFORMATION

We believe the statements technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. ** Chemical listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not listed [e] Animal data only
N/A = Not available N/D = Not determined

END OF MSDS DOCUMENT